View NSN Online: https://aerobasegroup.com/nsn/9150-00-966-8834

CITIES SERVICE COMPANY -- CITGO PACEMAKER 46 (FORMERLY PACEMAKER 20) 9150-00-966-8834

Product ID:CITGO PACEMAKER 46 (FORMERLY PACEMAKER 20)

MSDS Date:01/01/1985

FSC:9150

NIIN:00-966-8834

MSDS Number: BFZYB === Responsible Party ===

Company Name: CITIES SERVICE COMPANY

Emergency Phone Num: (918) 561-8856

CAGE:12518

=== Contractor Identification ===

Company Name: CITIES SERVICE CO Address:110 W 7TH

Box:300 City:TULSA State:OK ZIP:74102 Country:US CAGE:12518

======= Composition/Information on Ingredients ========

Ingred Name: REFINED PETROLEUM OIL (CAS NO: 64742-36-5)

Fraction by Wt: 99.0%

ACGIH TLV:5 MG/CUM (TWA)

Ingred Name: POLYDIMETHYLSILOXANE (10%) IN LIGHT MINERAL OIL-FOAM

INHIBITOR CAS:9016-00-6 RTECS #:TQ2690000

Fraction by Wt: 2 OZ, GASTRIC LAVAGE W/CUFFED

TUBE IS PREFERABLE TO EMESIS. SUBCUTANEOUS INJECTION REQUIRED PROMPT

SURGICAL DEBRIDEMENT. SEEK MEDICAL AIA IMMEDIATELY.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: NOT NORMALLY NEEDED UNLESS HOT VAPORS OR OIL MIST IS PRESENT (>TLV)

Ventilation: GOOD GENERAL VENT. EXPECIALLY IF HOT VAPORS/MIST IS PRESENT

Protective Gloves:RECOMMENDED

Eye Protection: IF SPLASHING IS POSSIBLE

Other Protective Equipment:BUTYL RUBBER, NEOPRENE. ETC. IF SKIN CONTACT IS PROBABLE.

Supplemental Safety and Health

CONFORMS TO MIL-H-

46001C, GRADE 2.UNIT OF ISSUE: 5 GALLON CAN. MFGS INDEX NO: TSIS-1079.VISCOSITY AT 100F:220 SUS. NFPA H-F-R CODES AS ASSIGNED BY MFR: 1-1-0.

======== Physical/Chemical Properties ==========

HCC:V6

Boiling Pt:B.P. Text:399C; 750F

Vapor Pres:< 1 Vapor Density:> 1 Spec Gravity:0.87

Evaporation Rate & Deference: