

GULF OIL COMPANY,U.S. -- HARMONY 68 (FORMERLY HARMONY 53) -- 9150-00-966-8835  
===== Product Identification =====

Product ID:HARMONY 68 (FORMERLY HARMONY 53)

MSDS Date:01/01/1985

FSC:9150

NIIN:00-966-8835

MSDS Number: BFZYJ

=== Responsible Party ===

Company Name:GULF OIL COMPANY,U.S.

Emergency Phone Num:(713) 651-0693

CAGE:GO897

=== Contractor Identification ===

Company Name:GULF OIL CO U.S. A DIV  
OF GULF OIL CORP

Box:1519

City:HOUSTON

State:TX

ZIP:77001

Country:US

CAGE:34252

Company Name:GULF OIL COMPANY - U.S.A.

CAGE:GO897

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM HYDROCARBON-LUBE OIL STOCK

ACGIH TLV:5 MG/CUM (MIST)

===== Hazards Identification =====

Effects of Overexposure:SKIN IRRIT,DERMATITIS.EYE

IRRIT.INHAL:HEADACHE,DIZZINESS,CNS DEPRESSION.

===== First Aid Measures =====

=====

First Aid:SKIN CONTACT:REMOVE CONTAMINATED CLOTHING & WASH W/SOAP &  
WATER.EYE CONTACT:FLUSH W/COPIOUS AMTS OF WATER.INHAL:REMOVE TO  
FRESH AIR.INGESTION:GIVE 2-4 OZ OF OLIVE OR VEGETABLE OIL & 1-2 OZ  
OF ACTIVATE D CHARCOAL.GET MEDICAL AID IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:218C; 425F PMCC

Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM ARE PREFERRED

Fire Fighting Procedures:USE FOAM & WATER SPRAY CAR

EFULLY TO AVOID  
EXCESSIVE FROTHING

Unusual Fire/Explosion Hazard:USE WATER TO COOL FIRE EXPOSED  
CONTAINERS.SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURE.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW,ELIMINATE SOURCES OF IGNITION,AVOID  
EXCESSIVE INHALATION & SKIN CONTACT.ABSORB WITH INERT MATERIAL SUCH  
AS SAND OR VERMICULITE.STORE IN CLOSED CONTAINERS PENDING  
DISPOSITION.OBSERVE GOVERNMENTAL SPILL & WATER QUAL  
ITY  
REGULATIONS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED.STORE  
AWAY FROM HEAT & OPEN FLAME.DO NOT STORE OR MIX W/STRONG  
OXIDANTS.WEAR OIL-IMPERVIOUS CLOTHING  
Other Precautions:AVOID SKIN CONTACT & INHALATION OF  
VAPORS,MISTS,FUMES.REMOVE CONTAMINATED CLOTHING PROMPTLY & LAUNDER  
BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AS  
S REQUIRED IF TLV IS EXCEEDED OR IF  
MISTS/SPRAYS ARE PRESENT  
Ventilation:AS NEEDED TO KEEP HOT VAPORS & MISTS BELOW TLV.  
Protective Gloves:RECOMMENDED  
Eye Protection:GOGGLES,SAFETY GLASSES  
Other Protective Equipment:APRON,ETC MADE OF BUTYL  
RUBBER,PVA,POLYETHYLENE,NEOPRENE  
Supplemental Safety and Health  
MIL-H-46001C,GRADE 3;UNIT OF ISSUE: 55 GAL DRUM.POUR POINT:-12C;  
10F.FIRE POINT: 268C;515F (COC).VAPOR PRESSURE IS NEGLIGIBLE.

===== Physical/Chemical Properties =====  
=====

HCC:V6  
Boiling Pt:B.P. Text:393C; 740F  
Vapor Density:>1  
Spec Gravity:0.8767  
Evaporation Rate & Reference:ESSENTIALLY ZERO  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:CLEAR,PALE-COLORED OIL  
Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS SUCH AS CHLORINE & CONCENTRATED OXYGEN.  
Stability Condition to Avoid:AVOID HIGH HEAT OR OPEN FLAME.  
Hazardous Decomposition Pr

products:CARBON MONOXIDE,CO\*2

===== Disposal Considerations =====

Waste Disposal Methods:OBSERVE FED,STATE & LOCAL REGULATIONS.WHEN  
DISPOSING OF LARGE QUANTITIES,RECLAMATION MAY BE COST EFFECTIVE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be a  
ccurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.