View NSN Online: https://aerobasegroup.com/nsn/9150-00-966-8837

Product ID:CITGO PACEMAKER 100 (FORMERLY PACEMAKER 60) MSDS Date:01/01/1985 FSC:9150 NIIN:00-966-8837 MSDS Number: BFZYQ === Responsible Party === Company Name: CITIES SERVICE COMPANY Emergency Phone Num: (918) 561-8856 CAGE:12518 === Contractor Identification === Company Nam e:CITIES SERVICE CO Address:110 W 7TH Box:300 City:TULSA State:OK ZIP:74102 Country:US CAGE:12518

Ingred Name:REFINED PETROLEUM OIL (CAS NO: 64742-36-5) Fraction by Wt: 99.0% ACGIH TLV:5 MG/CUM (TWA)

Ingred Name:POLYDIMETHYLSILOXANE (10%) IN LIGHT MINERAL OIL - FOAM INHIBITOR CAS:9016-00-6 RTECS #:TQ2690000 Fraction by Wt: 316C; >600F.

Spill Release Pr

ocedures:DIKE LARGE SPILLS. ABSORB WITH DIATOMACEOUS EARTH OR OTHER INERT MATERIAL. STORE IN CLOSED CONTAINERS UNTIL DISPOSITION. DO NOT ALLOW TO DRAIN TO SEWER. REPORT SPILLS TO APPROPRIATE AUTHORITY.

Handling and Storage Precautions: STORE IN STEEL TANK OR DRUM BELOW 120F. DOT HAZARD LABEL IS NOT REQUIRED. Other Precautions: FOR INGESTION OF AMTS > 2 OZ, GASTRIC LAVAGE W/CUFFED TUBE IS PREFERABLE TO EMESIS. SUBCUTANEOUS INJECTON REQUIRES PROMPT SURGICAL DEBRIDEMENT. SEEK MEDICAL AID IMMEDIATELY. Respiratory Protection:NOT NORMALLY NEEDED UNLESS HOT VAPORS OR OIL MIST IF PRESENT (>TLV) Ventilation: GOOD GENERAL VENT. ESPECIALLY IF HOT VAPORS/MIST IS PRESENT Protective Gloves:RECOMMENDED Eye Protection: IF SPLASHING IS POSSIBLE Other Protective Equipment: BUTYL RUBBER, NEOPRENE, ETC. IF SKIN CONTACT IS PROBABLE. Supplemen tal Safety and Health CONFORMS TO MIL-H-46001C, GRADE 4. UNIT OF ISSUE: 55 GALLON DRUM. MFRS INDEX NO: TSIS-1081. VISCOSITY AT 100F: 490 SUS. NFPA H-F-4 CODES AS ASSIGNED BY MFR: 0-1-0.

HCC:V6 Boiling Pt:B.P. Text:NO DATA Vapor Pres:1 Spec Gravity:0.8783 Evaporation Rate & amp; Reference: