View NSN Online: https://aerobasegroup.com/nsn/6850-00-967-1152

Product ID:REGULAR MINERAL SPIRITS; AMSCO SOLV 1005 MSDS Date:07/16/1987 FSC:6850 NIIN:00-967-1152 MSDS Number: BFZYW === Responsible Party === Company Name: UNOCAL CHEMICALS DIV: UNION OIL CO OF CALIFORNIA Address:1900 E. GOLF ROAD City:SCHAUMBURG State: L ZIP:60194-5021 Country:US Info Phone Num:312-490-2500 Emergency Phone Num:312-490-2500 CAGE:94684 === Contractor Identification === Company Name: UNOCAL CHEMICALS DIV., UNION OIL OF CALIFORNIA Address:1345 N MEACHAM Box:City:SCHAUMBURG State:IL ZIP:60196 Phone:312-490-2500/800-424-9300(CHEMTREC) CAGE:94684 Ingred Name:STODDARD SOLVENT CAS:8052-41-3 RTECS #:WJ8925000 Fraction by Wt: 100.0% **OSHA PEL:500 PPM** ACGIH TLV:100 PPM; 9

293

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:ACUTE:MAY CAUSE IRRITATION OF EYES,BURNING,TEARING & REDNESS;SKIN:IRRITATION,REDNESS,BURNING & DRYING,CRACKING;INHALATION:IRRITATION OF NOSE,THROAT AND CNS DEPRESSION;INGESTION:IRRITATION G.I.TRACT,DI ZZINESS,VOMITING,NAUSEA. CHRONIC:IRRITATION;DERMATITIS,LUNGS DAMAGE.

Effects of Overexposure:SEE HEALTH HAZARDS DA

## TA. Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN.

First Aid:EYES:FLUSH WITH PLENTY OF WATER;SEEK MEDICAL ATTENTION IF NEEDED. SKIN:WASH WITH SOAP AND WATER. INHALATION:REMOVE TO FRESH AIR;CALL A PHYSICIAN. INGESTION:DO NOT INDUCE VOMITING;CALL A PHYSICIAN AT O NCE.

Flash Point Method:TCC Flash Point:101F/38.3C L ower Limits:0.7 Upper Limits:6.0 Extinguishing Media:DRY CHEMICAL,CO\*2,FOAM. Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA. Unusual Fire/Explosion Hazard:THIS MATERIAL IS COMBUSTIBLE AND MAY BE IGNITED BY HEAT OR FLAMES.

Spill Release Procedures: USE PROPER PERSONAL PROTECTION; CONTAIN FREE LIQUID. USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

\_\_\_\_\_

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA;KEEP AWAY FROM HEAT AND OPEN FLAME.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE PEL/TLV. Ventilation:LOCAL/GENERAL TO MAINTAIN TLV/PEL. Protective Gloves:IMPERVIOUS. Eye Protection:CHEMICAL GOGGLES. Other Protective Equipment:EYE PROTECTION;FULL BODY COVER (LAB COAT, EYE-WASH, SAFETY SHOWER). Work Hygienic Practices: AVOID CONTACT WITH EYES AND SKIN; DONOT BREATHE VAPORS/MIST; WASH THOROUGHLY AFTER EACH USE. DO NOT EAT, DRINK/SMOKE IN WORK Supplemental Safety and Health PRODUCT CODE 11005 HCC:F4 Boiling Pt:B.P. Text:310-405F Vapor Pres:3.1 MMHG Vapor Density:4.9 Spec Gravity:0.788 Evaporation Rate & amp; Reference:0.12 (N-BUTYL-ACETATE=1) Solubility in Water:NEGL IGIBLE Appearance and Odor: CLEAR LIQUID, LITTLE IF ANY COLOR, CHARACTERISTIC ODOR. Percent Volatiles by Volume:100

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR BASES,OXIDIZING AGENTS AND SELECTED AMINES. Stability Condition to Avoid:OPEN FLAMES OR EXTREME HEAT. Hazardous Decomposition Products:CO AND/OR CO\*2.

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume re sponsibility for the suitability of this information to their particular situation.