

DOW CORNING CORP -- DOW CORNING(R) 200 FLUID, 50 CS -- 9150-00-970-5214

=====
Product Identification
=====

Product ID:DOW CORNING(R) 200 FLUID, 50 CS

MSDS Date:04/16/1990

FSC:9150

NIIN:00-970-5214

MSDS Number: BFZZY

=== Responsible Party ===

Company Name:DOW CORNING CORP

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency Phone

Num:517-496-5900

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICONE FLUID

CAS:63148-62-9

F

reaction by Wt: 100%
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT AVAILABLE
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.
Effects of Overexposure:EYE:MILD REDNESS SIMILAR TO WINDBURN.SKIN:NO KNOWN SYMPTOMS.INHALATION:NONE.INGESTION:LARGE AMOUNT MAY CAUSE DIGESTIVE DISCOMFORT.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

=====
===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH WITH WATER.SKIN:WIPE OFF AND FLUSH WITH WATER.INHALATION:NO FIRST AID SHOULD BE NEEDED.INGESTION:NO FIRST AID SHOULD BE NEEDED.

=====
===== Fire Fighting Measures =====

Flash Point Method:OC
Flash Point:545F,285C
Autoignition Temp:
Autoignition Temp Text:UNKNON
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AT ROOM TEMPERATURE WITH ADEQUATE VENTILATION. KEEP AWAY FROM FLAMES & HIGH TEMPERATURES.
Other Precautions:PRODUCT IS SENSITIVE TO CONTAMINATION AT ELEVATED TEMPERATURES.FLASH POINT MAY CHANGE IF CONTAMINATED BY STRONG ACIDS, BASES, SOME METALLIC COMPOUNDS AND OXIDIZING AGENTS.TRACES OF FORMALDEHYDE(CARCINOGEN)MAY PRODUCE IF HEATED >300F/149C.

===

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED

Ventilation:MECHANICAL(GENERAL) RECOMMENDED.

Protective Gloves:RUBBER AS REQUIRED.

Eye Protection:SAFETY GLASSES RECOMMENDED.

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplem

ental Safety and Health

DO NOT GET IN EYES OR ON CLOTHING.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres: