

MALLINCKRODT INC.,SCIENCE PRODUCT DIVISION -- ACETONE -- 6810-00-973-6473

=====  
Product Identification  
=====

Product ID:ACETONE

MSDS Date:09/05/1985

FSC:6810

NIIN:00-973-6473

MSDS Number: BGBCK

=== Responsible Party ===

Company Name:MALLINCKRODT INC.,SCIENCE PRODUCT DIVISION

Address:PARIS BYPASS

Box:M

City:PARIS

State:KY

ZIP:40361

Info Phone Num:314-982-5000

Emergency Phone Num:314-982-5000

CAGE:

62910

=== Contractor Identification ===

Company Name:MALLINCKRODT SPECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 100%

Other REC Limits:NONE

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====  
Hazards Ide

ntification =====

LD50 LC50 Mixture:LD50 ORAL RAT=9750MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:SEVERE

IRRITATION,REDNESS,PAIN;SKIN:IRRITATION,DEFATTING,REDNESS,PAIN,DRYING,CRACKING;IRRITATION TO NOSE,THROAT,MUCOUS MEMBRANES.DIZZINESS,DULLNESS,HEADACHE,NARCOTIC;INGESTION:NARCOTIC.SAME SYMPTOMS AS INHALATION. CHRONIC EXPOSURE:PROLONGED/REPEATED

S  
SKIN CONTACT MAY PRODUCE SEVERE IRRITATION OR DERMATITIS.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:USE OF ALCOHOLIC BEVERAGES ENHANCES TOXIC EFFECTS.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED;INGEST:IF SWALLOWED,GIVE TWO GLASSES OF WATER & INDUCE VOMIT.NOTHING BY MOUTH IF UNCON;SKIN/EYE EXPOSURE:RMV CONTMNTD CLOTHG.WASH SKIN W/SOAP & H\*2O .FLUSH SKIN/EYES W/LG H\*2O;GET MED HELPIMMEDIATLY

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:0F(-18C)

Autoignition Temp:Autoignition Temp Text:869F

Lower Limits:2.6

Upper Limits:12.8

Extinguishing Media:WATER,DRY CHEM,FOAM,CO\*2;WATER SPRAY:TO KEEP EXPD CANS COOL

Fire Fighting Procedures:USE H\*20 TO COOL EXPD CONTRS. USE SCBA & FULL PROT.CLTHG.

Unusual Fire/Explosion Hazard:ABOVE FLASH POINT,VAP-AIR MIXTURES ARE EXPLOSIVE WITHIN FLAMMABLE LIMITS; AUTO IGN TEMP:465C(869F)

===== Accidental Release Measures =====

Spill Release Procedures:RMV SOURCES OF IGN.USE PROTCTV EQUIP/CLOTHG.ISOLATE OR ENCLOSE LEAK/SPILL AREA.ABSORB SM SPILL W/COMM ABSORBNT &PLACE IN CLOSED CONTNR.DIKE LG SPILL W/DRY SAND OR EARTH & RECOVER LIQ FOR RECLAMATION W HEN POSSIBLE.SHOVEL ABSORBD SPILL INTO COVRD DRUM.

===== Handling and Storage =====

Handling and Storage Precaution

s:KEEP IN TIGHTLY CLOSED

CONTAINERS, STORED IN COOL, DRY, VENTILATED AREA. PROTECT AGAINST PHYSICAL DAMAGE. ISOLATE FM INCOMPATIBLE MATL, HEAT & SUNLIGHT, ETC.

Other Precautions: AVOID BREATHING VAP. KEEP CONTNR CLOSED. USE W/ADEQ VENT. DO NOT GET IN EYES, SKIN, OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLG. KEEP AWAY FM HEAT/FLAME. FOR TRNSFR LIQ, BOND & GROUND CONTNRS.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: SUPPLIED AIR RESPIR/SCBA; ESCAP

E: GAS MASK

Ventilation: LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves: IMPERVIOUS

Eye Protection: GOGGLES/FACE SHIELD

Other Protective Equipment: FULL PROTECTIVE CLOTHING, SAFETY SHOWER, EYE WASH STATION

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING. REMOVE AND LAUNDRER CONTAMINATED CLOTHING.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC: F2

Boiling Pt: B.P. Text: 56.5C (134F)

Melt/Freeze Pt: M.P/F.P Text: -139F (-95C)

Vapor P

res: 400 @ 103F

Vapor Density: 2.0

Spec Gravity: 0.8

Evaporation Rate & Reference: 7.7 (BUTYL ACETATE=1)

Solubility in Water: COMPLETE

Appearance and Odor: CLEAR, COLORLESS, VOLATILE LIQUID. FRAGRANT, MINT-LIKE ODOR.

Percent Volatiles by Volume: 100

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZERS, CHLOROFORM, ALKALIES, POTASSIUM T-BUTOXIDES, ACIDS.

Stability Condition to Avoid: HEAT, IGNITION SOURCES

Hazardous Decomposition Product

===== Disposal Considerations =====

Waste Disposal Methods: LG SPILL & LOT SIZES OF HAZ WASTE CAN BE ATOMIZED IN A RCRA APPRVD COMBUSTION CHAMBER OR DISPOSED OF IN A RCRA APPROVED LAND FILL FACILITY. DO NOT FLUSH TO SEWER. ENSURE COMPLIANCE W/ FED, STATE & LOCAL REGS; REPORTABLE QTY (RQ) (CWA/CERCLA): 5000 LBS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.