

GULF OIL CO, USA -- GULF CALIBRATING OIL 45A -- 6850-00-974-3738

=====
Product Identification
=====

Product ID:GULF CALIBRATING OIL 45A

MSDS Date:01/01/1987

FSC:6850

NIIN:00-974-3738

MSDS Number: BGBFH

=== Responsible Party ===

Company Name:GULF OIL CO, USA

Emergency Phone Num:713-651-0693

CAGE:MO418

=== Contractor Identification ===

Company Name:GULF OIL CO U.S. A DIV OF GULF OIL CORP

Box:1519

C

City:HOUSTON

State:TX

ZIP:77001

Country:US

CAGE:34252

Company Name:GULF OIL CO, USA

CAGE:MO418

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM HYDROCARBON(COMPLEX MIXTURE)

Fraction by Wt: 100%

=====
Hazards Identification
=====

Effects of Overexposure:PROLONGD/REPEATED CONTCT MAY CAUSE SKIN IRRIT/DERMATITIS;PROLONGD EXPOSURE TO MIST(SEE SUPPL DATA)

=====
First Aid Measures
=====

=====
=====

First Aid:SKIN:WASH W.SOAP & H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

=====
Fire Fighting Measures
=====

Flash Point:280F/138C (PM)

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY

Fire Fighting Procedures:USE WATER TO COOL EXPOSD CONTNRS,& TO FLUSH

SPILL AWAY

Unusual Fire/Explosion Hazard:SLIGHT WHEN EXPOSED TO HEAT.EMPTY

CONTAINERS MAY RETAIN PROD RESIDUE.NEVER CUT,DRILL NEAR FULL/EMPTY

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H₂O SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS:LG SPILL:DIKE W COMMERCIAL ABSORBENT,PUMP INTO COVERED DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED.KEEP AWAY FROM HEAT OR OPEN FLAME.DO NOT STORE OR MIX WITH STRONG OXIDANTS.

Other Precautions:AVOID SKIN CONTACT/INHALATION OF VAPORS,MISTS,FUMES;DO NOT WEAR OIL-SOILED CLOTHING.REMOVE OIL SOILED CLOTHING PROMPTLY & LAUNDRY BEFORE REUSE;PROMPTLY WASH SKIN W/SOAP & WATER AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST:AS REQUIRED FOR VAPOR,FUME,SMOKE

Protective Gloves:POLYETHYLENE

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:OIL IMPERVIOUS PROTECTIVE GARMENT IF CONTACT IS UNAVOIDABLE

Supplemental Safety and Health

OR FUMES MAY CAUSE IRRIT EYE/RESP TRACT;HEADACHE,DROW,DIZZ. INGEST:POSS GI IRRIT,DIARR.LIQUID:POSS EYE IRRIT. UPDATE PER NON-OSHA MSDS UNDATED RECD 24 MAY 85.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:510F/266C

Spec Gravity:0.8393

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, COLORLESS OIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS SUCH AS CHLORINE & CONCENTRATED OXYGEN.

Stability Condition to Avoid:AVOID IGNITION SOURCES

Hazardous Decomposition Products:CARBON MONOXIDE IN CASE OF INCOMPLETE CUMBUSTION.

===== Disposal Considerations =====

=====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use

e. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.