View NSN Online: https://aerobasegroup.com/nsn/6810-00-983-8551

Product ID: ISOPROPYL ALCOHOL, ANHYDROUS MSDS Date:12/11/1997 FSC:6810 NIIN:00-983-8551 MSDS Number: BGBMB === Responsible Party === Company Name: EXXON CHEMICAL AMERICAS Box:3272 **City:HOUSTON** State:TX ZIP:77001 Country:US Info Phone Num:713-870-6885 Emergency Phone Num:800-726-2015 Resp. Pa rty Other MSDS Num.:90275000 Preparer's Name:NOT PROVIDED Chemtrec Ind/Phone:(800)424-9300 CAGE:72190 === Contractor Identification === Company Name: EXXONMOBIL CHEMICAL CO, DIV OF EXXON MOBILCORP. Address:13501 KATY FWY Box:3272 City:HOUSTON State:TX ZIP:77253-3272 Country:US Phone:281-870-6000 / 800-726-2015 CAGE:72190

Ingred Name:ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 = Wt:100. Other REC Limits:NOT PROVI DED OSHA PEL:400 PPM OSHA STEL:500 PPM ACGIH TLV:400 PPM ACGIH STEL:500 PPM

LD50 LC50 Mixture:LD50 ORAL (RAT) 5840 MG/KG Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRITATING AND WILL INJURE EYE TISSUE IF NOT REMOVED PROMPTLY. SKIN: FREQUENT OR PROLONGED CONTACT MAY IRRITATE AND CAUSE DERMATITIS. INHALATION: VAPOR

CONCENTRATIONS ABOVE RECOMMENDED EXPOSURE LEVELS AR E IRRITATING TO

THE EYES AND THE RESPIRATORY TRACT, MAY CAUSE HEADACHES AND DIZZINESS, ARE ANESTHETIC AND MAY HAVE OTHER CENTRAL NERVOUS SYSTEM EFFECTS. NEGLIGLE HAZARD AT AMBIENT TEMPERATU RES (-18 TO 38 DEG C; 0 TO 100 DEF F). INGESTION: SMALL AMOUNTS OF THE LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHIOPNEUMONIA OR PULMONARY EDEMA. Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATION. SKIN:

IRRITATION,

DERMATITIS. INHALATION: IRRITATION, HEADACHES, DIZZINESS.

INGESTION: VOMITING.

Medical Cond Aggravated by Exposure:NOT PROVIDED

First Aid:EYE: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES. GET PROMPT MEDICAL ATTENTION. SKIN: IMMEDIATELY FLUSH WITH LARGE AMOUNT OF WATER; USE SOAP IF AVAILABLE. REMOVE CONTA MINATED CLOTHING, INCLUDING SHOES, AFTER FLUSHING HAS BE GUN.

INHALATION: USING PROPER RESPIRATORY PROTECTION, IMMEDIATELY REMOVE THE AFFECTED VICTIM FROM EXPOSURE. ADMINISTER ARTIFICIAL RESPIRATION IF BREATHING IS STOPPED. KEEP AT REST. CALL FOR PROMPT MEDICAL ATTENTION. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. KEEP AT REST. GET PROMPT MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:=11.7C, 53.F Autoignition Temp:>350.C, 662.F Lower Limits :2.0 Upper Limits:12.7 Extinguishing Media: EITHER ALLOW FIRE TO BURN UNDER CONTROLLED CONDITIONS OR EXTINGUISH WITH ALCOHOL TYPE FOAM AND DRY CHEMICAL. TRY TO COVER LIQUID SPILLS WITH FOAM. Fire Fighting Procedures: USE WATER SPRAY TO COOL FIRE EXPOSED SURFACES AND TO PROTECT PERSONNEL. SHUT OFF "FUEL" TO FIRE. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS. Unusual Fire/Explosion Hazard:FLAMMABLE LIQUID, CAN RELEASE VAPORS THAT FORM FLAMMABLE M IXTURES AT TEMPERATURES AT OR ABOVE FLASH POINT. Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. PREVENT ADDITIONAL DISCHARGE OF MATERIAL, IF POSSIBLE TO DO SO WITHOUT HAZARD. CONTAIN SPILL. IF IN PUBLIC AREA, KEEP PUBLIC AWAY AND ADVISE AUTHORITIES. PREVENT LIQUI D FROM ENTERING SEWERS, WATERCOURSES, OR LOW AREAS. CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS S UCH AS SAWDUST. RECOVER BY PUMPING OR WITH A SUITABLE ABSORBENT. Neutralizing Agent:NOT RELEVANT Handling and Storage Precautions: KEEP CONTAINER CLOSED. HANDLE AND OPEN CONTAINERS WITH CARE. STORE IN A COOL, WELL VENTILATED PLACE AWAY FROM INCOMPATIBLE MATERIALS. DO NOT HANDLE OR STORE NEAR AN OPEN FLAME, HEAT, OR OTHER SOURC ES OF IGNITION. PROTECT MATERIAL FROM DIRECT SUNLIGHT. Other Precautions:THIS MATERIAL IS NOT A STATIC ACCUMULATOR, BUT USE PROPER GROUNDING PROCEDURES. DO NOT PRESSURIZE, CUT, HEAT, OR WELD CONTAINERS. EMPTY PRODUCT CONTAINERS MAY CONTAIN PRODUCT RESIDUE.

RECONDITIONING.

DO NOT REUSE EMPTY CONTAINERS WITHOUT COMMERCIAL CLEANING OR

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORS MAY BE NECESSARY TO PREVENT OVEREXPOSURE BY INHALATION. Ventilation:USE OF MECHANICAL DILUTION VENTILATION IS RECOMMENDED FOR CONFINED SPACES, OR PRODUCT HEATED OR AGITATED. USE EXPLOSION-PROOF MECHANICAL VENTILATION EQUIPMENT. Protective Gloves: WHERE CONTACT IS LIKELY, WEAR CHEMICAL RESISTANT GLOVES. Eye Protection: WHERE CONTACT MAY OCCUR, WEAR SAFETY GLASSES WITH SIDE SHIELDS/CHEMICAL GOGGLES Other Protective Equipment: FOR OPEN SYSTEMS WHERE CONTACT IS LIKELY, WEAR LONG SLEEVES. Work Hygienic Practices:NOT PROVIDED Supplemental Safety and Health ABBREVIATION: N/A = N OT APPLICABLE. N/AV = NOT AVAILABLE. N/K = UNKNOWN. N/P = NOT PROVIDED. N/R = NOT RELEVANT. N/D = NOT DETERMINED. N/E = NOT ESTABLISHED.HCC:F2 NRC/State Lic Num:NOT RELEVANT Boiling Pt:B.P. Text:180-181F Melt/Freeze Pt:=-88.7C, -128.F Decomp Temp:Decomp Text:NOT PROVIDED Vapor Pres:36@ 212F Vapor Density:>1 Spec Gravity:0.79 Viscosity:2.2 CST @ 68F Evaporation Rate & amp; Reference: 2.3 (N-BU ACETATE = 1) Solubility in Water:100% @ 68F Appearance and Odor:CLEAR,COLORLESS LIQUID Percent Volatiles by Volume:100 Corrosion Rate:NOT PROVIDED

 Stability Indicator/Materials to Avoid:YES
CAUSTICS, AMINES, ALKANOLAMINES, ALDEHYDES, STRONG OXIDIZING AGENTS, AND CHLORINATED COMPOUNDS.
Stability Condition to Avoid:MODERATE RISK OF PEROXIDE FORMATION.
MODERATE PEROXIDE HAZARD ON STORAGE AND CONCENTRATION. INHIBITOR NOT BEEN ADDED TO MITIGAT

## E PEROXIDE HAZARD. Hazardous Decomposition Products:NONE

Toxicological Information:EYE: IRRITATING AND WILL INJURE EYE TISSUE IF NOT REMOVED PROMPTLY. SKIN: FREQUENT OR PROLONGED CONTACT MAY IRRITATE AND CAUSE DERMATITIS. INHALATION: VAPOR CONCENTRATIONS ABOVE RECOMMENDED EXPOSURE LEVELS ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT, MAY CAUSE HEADACHES AND DIZZINESS, ARE ANESTHETIC AND MAY HAVE OTH

ER CENTRAL NERVOUS SYSTEM EFFECTS. NEGLIGLE HAZARD AT AMBIENT TEMPERATU RES (-18 TO 38 DEG C; 0 TO 100 DEF F). INGESTION: SMALL AMOUNTS OF THE LIQUID ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION, OR FROM VOMITING, MAY CAUSE BRONCHIOPNEUMONIA OR PULMONARY EDEMA.

Ecological:NO SPECIFIC ECOLOGICAL DATA AVAILABLE.

Waste Disposal Meth

ods:CONSULT AN EXPERT ON DISPOSAL OF RECOVERED MATERIAL AND ENSURE CONFORMITY TO LOCAL DISPOSAL REGULATIONS.

Transport Information: DEPARTMENT OF TRANSPORTATION (DOT): DOT SHIPPING DESCRIPTION: ISOPROPANOL, CLASS 3, UN 1219, PG II.

SARA Title III Information: UNDER SECTIONS 311/312 OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT, THIS PRODUC

T IS CLASSIFIED INTO THE FOLLOWING HAZARD CATEGORIES: IMMEDIATE HEALTH, DELAYED HEALTH, FIRE. THIS INFORMATION MA Y BE SUBJECT TO THE PROVISIONS OF THE COMMUNITY RIGHT-TO-KNOW REPORTING REQUIREMENTS (40 CFR 370) IF THRESHOLD QUANTITY CRITERIA ARE MET.

Federal Regulatory Information: THIS PRODUCT IS LISTED ON THE TSCA INVENTORY AT CAS REGISTRY NUMBER 67-63-0. IF THIS PRODUCT IS ACCIDENTALLY SPILLED, IT IS NOT SUBJECT TO ANY SPECIAL REPORTING UNDER THE REQUIREMENTS OF TH E COMPREHEN SIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT (CERCLA). MANUFACTURER RECOMMENDS CONTACTING LOCAL AUTHORITIES TO DETERMINE IF THERE MAY BE OTHER LOCAL REPORTING REQUIREMENTS. State Regulatory Information:NOT PROVIDED

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States o f America in no manner whatsoever.

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.