View NSN Online: https://aerobasegroup.com/nsn/9150-00-985-7248 EXXON COMPANY -- 5114 EP GREASE -- 9150-00-985-7248 ============= Product Identification ================= Product ID:5114 EP GREASE MSDS Date:01/01/1985 FSC:9150 NIIN:00-985-7248 MSDS Number: BGBVQ === Responsible Party === Company Name: EXXON COMPANY Emergency Phone Num:713-656-3424 CAGE:72447 === Contractor Identification === Company Name: EXXON COMPANY U.S.A. Box:2180 City:HOUSTON State:TX ZIP:77252-2180 Country:U Phone:713-656-5949 / 713-656-3424 CAGE:29700 Company Name: EXXON COMPANY, U.S.A. Address:ROOM 2344 Box:2180 City:HOUSTON State:TX ZIP:77252-2180 Country:US Phone:713-656-5949 CAGE:72447 ======= Composition/Information on Ingredients ======== Ingred Name:LITHIUM SOAP Ingred Name: SYNTHETIC ESTERS Effects of Overexposure: EYE? SKIN: IREITATION. INJECTION OF G4EASE INTOSKIN:SOFT TISSUE DAMAGE.

\_\_\_\_\_

===== First Aid Measures ====================================
First Aid:EYE: FLUSH WTH WATER 15 MINUTES. SKIN:WASH WITH SOAP 6 WATER. INJECTION UNDER THE SKIN:CONTACT PHYSICIAN IMMEDIATELY.
======================================
Flash Point:415F/212C (COC) Lower Limits:1 Upper Limits:7 Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATER FOG OR SPRAY. Fire Fighting Procedures:SELF-CONT BREATH APP,WATER SPRAY TO COOL EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard:DO
NOT MIX OR STORE WITH STRONG OXIDANTS.
========== Accidental Release Measures ============
Spill Release Procedures:RECOVER FREE LUBRICANT. ADD ABSORBENT OUT OF SEWERS & WATER COURSES BY DIKING OR IMPOUNDING.
======================================
Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.  DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.  Other Precautions:AVOID BREATHING OIL MIST. LAUNDER OIL
SOAKED CLOTHING BEFORE REUSE.DISCARD LUBRICANT-SOAKED SHOES.
======= Exposure Controls/Personal Protection =========
Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN. Ventilation:LOCAL Protective Gloves:CHEM RESISTANT Eye Protection:SPLASH GOGGLE/FACE SHIELD Other Protective Equipment:CHEM RESISTANT APRON,COUERALLS Supplemental Safety and Health CONTAINER SIZE: 35 LB CAN
======================================

=====

HCC:V6
Boiling Pt:B.P. Text:>500F/260C
Vapor Density:>10
Spec Gravity:0.94
Evaporation Rate & Description Reference: