View NSN Online: https://aerobasegroup.com/nsn/9150-00-985-7255

KAL-GARD COATING AND MFG CORP -- "FA" PER MIL-L-8937D -- 9150-00-985-7255

Product ID: "FA" PER MIL-L-8937D

MSDS Date:11/12/1990

FSC:9150

NIIN:00-985-7255

MSDS Number: BGBWF === Responsible Party ===

Company Name: KAL-GARD COATING AND MFG CORP

Address:16616 SCHOENBORN ST

City:SEPULVEDA

State:CA

ZIP:91343-6106 Country:US

Info Phone Num:818-894-3615

Emergency Phone N

um:800-424-9300 (CHEMTREC) Preparer's Name:NOT READABLE

CAGE:9G654

=== Contractor Identification ===

Company Name: KAL-GARD COATING AND MFG CORP

Address:16616 SCHOENBORN ST

Box:City:SEPULVEDA

State:CA

ZIP:91343-6106

Country:US

Phone:818-894-3615

CAGE:9G654

Company Name: SANCHEZ & ASSOCIATES

Address:476 WEST FOGG STREET

Box:1649

City:COLTON (MAY BE OUT OF BUSINESS!)

State:CA ZIP:92324 Country:US

Phone:714-370-3921/FAX824-0341 ALL WRONG#

CAGE:0HF19

====== Composition/Information on Ingred

ients ========

Ingred Name: ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000 Fraction by Wt: 4.90%

Other REC Limits: NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000 Fraction by Wt: 4.90%

Other REC Limits:NONE SPECIFIED OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: MOLYBDENUM DISULFIDE

CAS:1317-33-5 RTECS #:QA4697000

Fr

action by Wt: 29.2%

Other REC Limits: NONE SPECIFIED

Ingred Name: ANTIMONY (SARA III)

CAS:7440-36-0

RTECS #:CC4025000 Fraction by Wt: 18.2%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.5 MG/M3

ACGIH TLV:0.5 MG SB/M3; 9192

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:BASIC LEAD PHOSPHITE

CAS:12141-20-7 Fraction by Wt: 6.60%

Other REC Limits: NONE SPECIFIED

========= Hazards Identification ==================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports

of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES:SEVERE PAIN AND CONJUNCTIVAL IRRITATION, POSSIBLE CORNEAL DAMAGE. SKIN:SEVERE PAIN AND IRRITATION, POSSIBLE BURNS AND MARKED DERMATITIS. INHALATION: RESPIRATORY SYSTEM IRRITATION AND POSSIBLE PULM ONARY Effects of Overexposure: EYES: EXCESS TEAR PRODUCTION, BLINKING, AND EXCESS REDNESS. SKIN:POSSIBLE SKIN BURNS, EXCESS REDNESS AND SWELLING MAY RESULT. INHALATION:BURNING SENSATION OF EYE S. NOSE AND THROAT, CHEST DISCOMFORT, SN EZING, COUGHING, NAUSEA, CNS SYMPTOMS, CYANOSIS. INGESTION: PAIN IN THE THROAT, CHEST, AND ABDOMEN WITH CNS SYMPTOMS. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER. First Aid:EYES:IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MIN. WHILE HOLDING EYELIDS OPEN. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN THOROUGHLY WITH SOAP AND WAT ER. INHALATION: REMOVE VICTI M TO FRESH AIR AND RESTORE BREATHING IFNECESSARY. INGESTION: IF VICTIM IS CONSCIOUS, GIVE MILK, EGG WHITES, VEGETABLE OIL IF AVAILABLE. DO NOT INDUCE VOMITING. CONTACT A PHYSICIAN IMMEDIATELY. Flash Point:22.0F.-5.6C Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL OR FOAM. Fire Fighting Procedures: USE WATER SPRAY OR FOG TO COOL FIRE-EXPOSED CONTAINERS. Unusual Fire/Explosion Haz ard: VAPORS CAN FLOW TO IGNITION SOURCES AND FLASHBACK. ======== Accidental Release Measures =========== Spill Release Procedures: REMOVE HEAT AND IGNITION SOURCES; VENTILATE AREA; CLEAN UP WITH INERT ABSORBANT. AVOID DISCHARGE TO SEWERS, SOIL AND WATERWAYS. WEAR PROTECTIVE EQUIPMENT.

============= Handling and Storage ==========================

FIRE RISK AREA. PROTECT FROM PHYSICAL

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED, LOW

DAMAGE.KEEP CONTAINERS

CLOSED. MAINTAIN STRICT HYGIENE FOR CHEM HANDLING.

Other Precautions:PER MFR,THIS PRODUCT CONTAINS SMALL AMOUNTS OF LEAD WHICH IS CUMULATIVE POISON.AVOID SKIN,EYES,CLOTHING CONTACT.RMV & LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.AVOID OPEN FLAMES.

====== Exposure Controls/Personal Protection ========

Respiratory Protection:WEAR NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPORS.

Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.

Protective

Gloves: IMPERVIOUS

Eye Protection: GOGGLES/FACE SHIELD

Other Protective Equipment:FULL PROTECTIVE CLOTHNG,STEEL-TOED

SHOES, WORK GLOVES

Work Hygienic Practices: GOOD PERSONAL HYGIENE IS ESSENTIAL.

Supplemental Safety and Health

NONE

======== Physical/Chemical Properties ==========

HCC:F2

Boiling Pt:B.P. Text:171F,77C

Melt/Freeze Pt:M.P/F.P Text:LIQUID

Vapor Pres:>43 Vapor Density:>1 Spec Gravity:.82

Evaporation Rate & Dry Reference: