
View NSN Online: https://aerobasegroup.com/nsn/9150-00-985-7293
PENRECO PETROTECT VAP-MIL-P-46002,CODE 4085 9150-00-985-7293 ====================================
Product ID:PETROTECT VAP-MIL-P-46002,CODE 4085 MSDS Date:01/01/1985 FSC:9150 NIIN:00-985-7293 MSDS Number: BGBWV === Responsible Party === Company Name:PENRECO Emergency Phone Num:412-445-2687 CAGE:6B796 === Contractor Identification === Company Name:PENRECO Address:700 MILIAM ST PENNZOIL PL Box: 2967 City:HOUSTON State:TX ZIP:77252 Country:US CAGE:6B796
======= Composition/Information on Ingredients ========
Ingred Name:LUBRICATING OIL,PRESERVATIVE,CORROSION INHIBITED. ACGIH TLV:UNK
============ Hazards Identification ============
Effects of Overexposure:EYES:BURINING & IRRITATION;SKIN:IRRITATION/DERMATITIS;INHALATION;IRR/DORWSINESS/COM A;ING:IRR/MON,STO
======================================
First Aid:EYES:FLU SH W/LARGE AMT OF WATER.CONTINUE AT LEAST 15 MIN.CALL DR.SKIN:REMOVE ALL CONT.CLTHG,WASH SKIN W/SOAP & WATER.INHAL:REMOVE TO FRESH AIR,IF BREATHING HAS STOPPED,APPLY ARTIFICAL RESPIR & GIVE O* 2,IF RCQD. CALL DR; ING:DO NOT INDUCE VOMTG.
======================================
Flash Point:240F Autoignition Temp:Autoignition Temp Text:>600F
========== Accidental Release Measures ===========
Spill Release Procedures:SCRAPE UP MATERIAL I



======== Physical/Chemical Properties ===========

HCC:V6

Boiling Pt:B.P. Text:400F

Vapor Pres:1.0 Spec Gravity:0.90

Evaporation Rate & Deference: