

J.W. HARRIS CO.,INC. (UNIBRAZE CORP.) -- SAFETY SILV 45 -- 3439-00-988-3882

=====
Product Identification
=====

Product ID:SAFETY SILV 45

MSDS Date:01/01/1987

FSC:3439

NIIN:00-988-3882

MSDS Number: BGBYT

=== Responsible Party ===

Company Name:J.W. HARRIS CO.,INC. (UNIBRAZE CORP.)

Emergency Phone Num:513-891-2000

CAGE:27911

=== Contractor Identification ===

Company Name:J. W. HARRIS CO., INC.

Address

Address:10930 DEERFIELD ROAD

Box:City:CINCINNATI

State:OH

ZIP:45242-4110

Country:US

Phone:513-891-2000

CAGE:27911

=====
Composition/Information on Ingredients
=====

Ingredient Name:SILVER (SARA III)

CAS:7440-22-4

RTECS #:VW3500000

Fraction by Wt: 45%

OSHA PEL:0.01 MG/M3

ACGIH TLV:0.1 MG/M3; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingredient Name:COPPER (SARA III)

CAS:7440-50-8

RTECS #:GL5325000

Fraction by Wt: 30%

OSHA PEL:0.1MG/M3 FUME/1 DUST

ACGIH TLV:0.2MG/M3 FUME; 9192

EPA Rpt Qty:5

000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ZINC (SARA III)
CAS:7440-66-6
RTECS #:ZG8600000
Fraction by Wt: 25%
OSHA PEL:10 MG ZNO/M3
ACGIH TLV:10 MG ZNO/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:COPPER&ZINC FUME MAY CAUSE METAL FUME
FEVER.SHORT TERM-SYMP-METALLIC TASTE,DRY/IRRIT (SEE SUPP DATA)

===== First Aid Measures =====

First Aid:REMOVE FROM DUST OR FUME EXPOSURE. IF BREATHING HAS
STOPPED,PERFORM ARTIFICIAL RESPIRATION. SUMMON MEDICAL AID
IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:NONFLAMMABLE
Extinguishing Media:NONFLAMMABLE
Fire Fighting Procedures:NONFLAMMABLE
Unusual Fire/Explosion Hazard:(NONFLAMMABLE) OPEN FLAME & SPARKS CAN
IGNITE COMBUSTIBLES,SEE ANSI/ASC Z49.1-1983 SECTION 6.

===== Accidental Release Measures =====

Spill Release Procedures:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:READ & UNDERSTAND MFR'S INSTRUCTNS &
PRECAUTIONARY LABEL ON PRODUCT.SEE AMERICAN NATIONAL STD Z49.1,SFTY
IN WELDING&CUTTING,&OSHA PUB 2206 (29CFR1910)
Other Precautions:POSS USED W/FLUORIDE TYPE FLUX.IF APPLIC,CONSIDER
FLUX FUME IN HAZ EVAL.HAZ DECOMP:ZINC(OXIDE).FLUX COATED,ALSO BORIC
ACID(BORON
OXIDE,TLV=10MG/CUM,PEL=15MG/CUM);FLUORIDES,TLV&PEL=2.5MG

(F)/CUM

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRABLE FUME
RESPIRATR/AIR SUPPLIED RESPIRATR

Ventilation:ENOUGH VENT,LOC EXHAUST AT FLAME TO KEEP FUMES&GASES <
TLV'S

Protective Gloves:WELDER'S GLOVES

Eye Protection:FILTER LENS-PROPER SHADE#

Other Protective Equipment:ARM PROTECTORS,APRONS,HATS,SHOULDER
PROT,DARK STURDY CLOTHES

Supplemental Safety and Health

THROAT W/COUGH,SHORT BREATH,NAUSEA,FEVER,ACHE,CHILL

.PULMONARY

IRRIT/PNEUMOCONIOSIS POSS W/LONG TERM EXP TO WELD

FUME,GAS,DUST.FUME IRRIT MAY AGGRAVATE LUNG ILLNESSES.PRIM EXP

ROUTE-FUME INHAL.

=====
===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:SOLID WIRE/ROD.ROD POSS COAT W/CHEM FLUX-BLUE/OTHR

=====
===== Stability and Reactivity Data =====

Hazardous Decomposition Products:SILVER (METAL & SOLUBLE CMPDS),COPPER
(FUME),(SEE OTHR PREC)

=====
===== Dispos
al Considerations =====

Waste Disposal Methods:WASTE DISPOSAL MUST BE IN ACCORDANCE
W/FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document shou

Id seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.