View NSN Online: https://aerobasegroup.com/nsn/8010-00-990-8256

Product ID:PT-535 B MSDS Date:01/01/1987 FSC:8010 NIIN:00-990-8256 **MSDS Number: BGCDF** === Responsible Party === Company Name: PRODUCTS/TECHNIQUES, INC. Emergency Phone Num:213-770-3600 CAGE:06341 === Contractor Identification === Company Name: PRODUCTS/TECHNIQUES INC Address:3271 S RIVERSIDE AVE Box:City:RIAL TO State:CA ZIP:92376 Country:US Phone:909-877-3951 CAGE:06341

Ingred Name:EPOXY RESIN Fraction by Wt: 50.0%

Ingred Name:N-BUTYL ALCOHOL (SARA III) CAS:71-36-3 RTECS #:EO1400000 Fraction by Wt: 25.0% OSHA PEL:100 PPM ACGIH TLV:S, C 50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:GLYCOL ETHER CAS:111-46-6 RTECS #:ID5950000 Fraction by Wt: 25.0% ACGIH TLV:200 PPM

Ingred Name: POLYAMIDE RESIN

Ingred Name:C

ARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Fraction by Wt: 1.0% OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192
======================================
Effects of Overexposure:HEADACHE,NAUSEA,ANESTHESIA,DIZZY,LIQUID MODERATELY IRRITATING TO SKIN & EYES.
======================================
First Aid:INHAL: MOVE TO FRESH AIR. RESTORE BREATHING IF NEEDED. SKIN:FLUSH WITH SOAP & WATER. EYES:FLUSH WITH PLENTY OF WATER.
======================================
Flash Point:106 F, 41 C TOC Lower Limits:1.0 Extinguishing Media:FOAM,CO*2 Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE
======================================
Spill Release Procedures: AVOID OPEN FLAME OR SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. ABSORB WITH SWEEPING COMPOUND.
======================================
Handling and Storage Precautions:KEE P IN COOL DRY AREA,PROVIDE ADEQUATE VENTILATION.
======== Exposure Controls/Personal Protection ====================================
Respiratory Protection:ORGANIC VAPOR MASH Ventilation:LOCAL EXHAUST DESIRABLE,APPROVED CLASS D MECHANICAL Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES Supplemental Safety and Health
======================================
HCC:F4 Boiling Pt:B.P. Text:240 F,116 C Spec Gravity:1.1 Evaporation Rate & amp; Reference:< ETHER Solubility in Wa

ter:NEGLIGIBLE Appearance and Odor:SLIGHT BUTYL ALCOHOL ODOR. Percent Volatiles by Volume:50.0

Stability Indicator/Materials to Avoid:YES NONE Hazardous Decomposition Products:NONE

Waste Disposal Methods: EVAPORATE OR FLUSH WITH WATER TO OPEN, WELL VENTILATED AREA. USE OIL SEWER IF AVAILABLE-REMOVE TO INCINERATOR. FOLLOW LOCAL EPA REGULATIONS.

Disclai

mer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.