

SUN PETROLEUM PRODUCTS COMPANY(MFR)LIVINGSTON (VEN -- SUNVIS 747 (SUN
CODE:142200) -- 9150-00-993-6621

=====
Product Identification
=====

Product ID:SUNVIS 747 (SUN CODE:142200)

MSDS Date:01/01/1987

FSC:9150

NIIN:00-993-6621

MSDS Number: BGCFY

=== Responsible Party ===

Company Name:SUN PETROLEUM PRODUCTS COMPANY(MFR)LIVINGSTON (VEN

Emergency Phone Num:215-447-1852

CAGE:SUNPE

=== Contractor Identifi

cation ===

Company Name:SUN PETROLEUM PRODUCTS COMPANY

CAGE:SUNPE

Company Name:SUN PIPE LINE CO

Address:907 S DETROIT AVE

Box:2039

City:TULSA

State:OK

ZIP:74120-4225

Country:US

CAGE:87612

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT REFINED HEAVY PARAFFINIC DISTILATE OIL,CAS#64741884
(USE TLV AS OIL MIST)

Fraction by Wt: 98.2%

ACGIH TLV:5MG/CUM(OILMIST)

Ingred Name:ZINC DITHIO PHOSPHATE (SEE SUPP.DATA)

CAS:19210-06-1

RTECS #:TE4800000

Fraction

by Wt: U/K

Ingred Name:BARIUM SULFONATE

CAS:25619-56-1

RTECS #:CR0700000

Fraction by Wt: U/K

OSHA PEL:0.5 MG/M3 (BA)

ACGIH TLV:0.5 MG/M3 (BA); 8990

Ingred Name:METHACRYLATE COPOLYMER

Fraction by Wt: U/K

ACGIH TLV:NOT SPECIFIED

Ingred Name:SILICONE POLYMER

Fraction by Wt: TRAC

ACGIH TLV:NOT SPECIFIED

=====
Hazards Identification
=====

Effects of Overexposure:EYE/SKIN: IRRITATION.

d:EYE:FLUSH WITH WATER 15 MINUTES. SKIN:WASH WITH SOAP & WATER,WASH CLOTHES BEFORE REUSE. INGESTION:GIVE LIQUID & INDUCE VOMITING. SMALL AMOUNTS IN MOUTH,RINSE WITH WATER UNTIL NO TASTE OF PRODUCT REMAINS.

===== Fire Fighting Measures =====

Flash Point:380F/193C(COC)
Autoignition Temp:Autoignition Temp Text:700F
Extinguishing Media:WATER FOG, CHEMICAL FOAM, DRY CHEMICAL,CO*2
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP USING AN OIL ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:STORAGE PER NFPA CLASS IIIB LIQUID.
Other Precautions:AVOID CONTACT WITH SKIN & EYES.DO NOT INHALE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS OR OIL MIST.
Ventilation:MECHANICAL
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES
Other Protective Equipment:IMPERVIOUS CLOTHING.
Supplemental Safety and Health
TYPICALLY CONTAINS:0.083% BARIUM; 0.056% ZINC AND 0.052% PHOSPHORUS.
CONTAINER SIZE: 55 GAL DRUM.

===== Physical/Chemical Properties =====

HCC:V6
Vapor Density:15
Spec Gravity:0.87
Evaporation Rate & Reference:1000X SLOWER ETHER
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIGHT AMBER FLUID,LITTLE ODOR

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZES

Hazardous Decomposition Products: CARBON MONOXIDE & ASPHYXIANTS

===== Disposal Considerations =====

Waste Disposal Methods: LOCAL, STATE AND FEDERAL REGULATIONS COVER
DISPOSAL OF CHEMICAL WASTE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of

Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.