View NSN Online: https://aerobasegroup.com/nsn/8040-00-994-1696

EMERSON AND CUMING, INC. -- STYCAST 2762 BLACK -- 8040-00-994-1696

Product ID:STYCAST 2762 BLACK MSDS Date:01/01/1987 FSC:8040 NIIN:00-994-1696 **MSDS Number: BGCGJ** === Responsible Party === Company Name: EMERSON AND CUMING, INC. Emergency Phone Num:617-935-4850 CAGE:OB562 === Contractor Identification === Company Name: EMERSON AND CUMING, INC, Address:77 DRAGON CT. С ity:WOBURN State:MA ZIP:01888-5000 Country:US Phone:617-935-4850/617-938-8630 CAGE:OB562 Company Name: GRACE W R & CO EMERSON & CUMING DEWEY & ALMY CHEM Address:869 WASHINGTON ST **City:CANTON** State:MA ZIP:02021-2513 Country:US Phone:617-935-4850 CAGE:04552

Ingred Name:N-BUTYL GLYCIDYL ETHER (BGE) CAS:2426-08-6 RTECS #:TX4200000 Fraction by Wt: 98% ACGIH TLV:NOT SPECIFIED

============ Hazards Identification ========

Reports of Carcinogenicity:NTP:NO IA	RC:YES OSHA:NO
Explanation of Carcinogenicity:NTP LIST	S EPICHLOROHYDRIN AS PROPOSED
FOR ADDITION TO ITS 5TH ANNUAL	. REPORT AS REASONABLY ANTICIPATED
CARCINOGEN.	

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

Extinguishing Media:CO*2,DRY CHEMICAL,FOAM,WATER FOG Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.

Unusual Fire/Explosion Hazard:TOXIC FUMES MAY BE EVOLVED UPON EXPOSURE TO HEAT OR OPEN FLAMES.

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;DIKE AREA TO PREVENT SPREADING;USE SUITABLE ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

 Handling and Storage Precautions:STORE IN COOL,DRY PLACE;KEEP AWAY FROM HEAT OR OPEN FLAME;KEEP CONTAINER CLOSED WHEN NOT IN USE.
Other Precautions:AVOID CONTACT WITH SKIN,EYES AND CLOTHES;DO NOT INHAL VAPORS/MIST.

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:USE NIOSH/MSHA APPRVD RESPIRATOR FOR ORG.VAPOR/MIST OR SCBA IF > TLV Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 1.0 Spec Gravity:2.65 Solubility in Water:NEGLIGIBLE Appearance and Odor:BLACK PASTE Percent Volatiles by Volume:NEGL

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS,AMINES,AMIDES,MINERAL ACIDS,THIOSULFATES. Stability Condition to Avoid:EXTREME HEAT,OPEN FLAMES Hazardous Decomposition Products:CO,CO*2,OXIDES OF NITROGEN. Conditions to Avoid Polymeriz ation:EXPOSURE TO INCOMPATIBLE SUBSTANCES.

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.