

ALLOY RODS CORPORATION -- ER-308 ELC CL2 0.062 -- 3439-00-995-9724

=====
Product Identification
=====

Product ID:ER-308 ELC CL2 0.062

MSDS Date:07/24/1986

FSC:3439

NIIN:00-995-9724

MSDS Number: BGCJN

=== Responsible Party ===

Company Name:ALLOY RODS CORPORATION

Address:WILSON AVENUE

Box:517

City:HANOVER

State:PA

ZIP:17331

Info Phone Num:717-637-8911

Emergency Phone Num:717-637-8911

CAGE:84021

===

Contractor Identification ===

Company Name:ESAB GROUP INC

Address:801 WILSON AVENUE

Box:517

City:HANOVER

State:PA

ZIP:17331

Country:US

Phone:717-637-8911 OR 800-933-7070

CAGE:84021

=====
Composition/Information on Ingredients
=====

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Other REC Limits:5MG/M*3

OSHA PEL:10MG/M*3

ACGIH TLV:5MG/M*3

Ingred Name:NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR5950000

Other REC Limits:1MG/M*3

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

Ingred

Name:CALCIUM FLUORIDE
CAS:7789-75-5
RTECS #:EW1760000
Other REC Limits:2.5MG/M*3
OSHA PEL:2.5 MG/M3 (F)
ACGIH TLV:2.5 MG/M3 (F); 8990

Ingred Name:SODIUM SILICATE
CAS:6834-92-0
RTECS #:VV9275000
Other REC Limits:10MG/M*3(NUISANCE D)
OSHA PEL:10MG/M*3(RESP DUST)
ACGIH TLV:0.1MG/M*3(RESP DUST)

Ingred Name:BENTONITE (AS NUISANCE DUST OR PARTICULATES NOT OTHERWISE REGULATED)
CAS:1302-78-9
RTECS #:CT9450000
OSHA PEL:15 MG/M3 TOTAL DUST
ACGIH TLV:10 MG/M3 TDUST;8990

Ingred Name:CHROMIUM (SARA III)
CAS:7440-47-3
RTECS #:GB4200000
Other REC Limits:0.5MG/M*3
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:MANGANESE (SARA III)
CAS:7439-96-5
RTECS #:OO9275000
Other REC Limits:5MG/M*3 (C)
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)
CAS:1317-65-3
RTECS #:EV9580000
Other REC Limits:10MG/M*3
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:SILICA, CRYSTALLINE - QUARTZ
CA

S:14808-60-7
RTECS #:VV7330000
Other REC Limits:0.1MG/M*3(RESP DUST)
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:POTASSIUM SILICATE
CAS:1312-76-1
OSHA PEL:10MG/M*3(RESP DUST)
ACGIH TLV:0.1MG/M*3(RESP DUST)

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES
Health Hazards Acute and Chronic:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNESS
OF CHEST,FEVE
R, DIZZINESS, DRYNESS, IRRITATION OF EYES, NOSE & THROAT.
CHRONIC: EXCESSIVE LEVELS MAY CAUSE BRONCHIAL ASTHMA, LUNG
FIBROSIS, SIDEROSIS. ARC RAYS CAN INJUR E EYES & BURN SKIN. ELECTRIC
SHOCK CAN KILL.
Explanation of Carcinogenicity:CHROMIUM VI IS A HUMAN CARCINOGEN.
CHROMIUM III IS A SUSPECTED HUMAN CARCINOGEN. NI IS A SUSPECTED
HUMAN CARCINOGEN.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY
OR ALLERGIC CONDI
TIONS. HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG
SMOKERS.

=====
===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE & OBTAIN PROMPT MEDICAL ATTENTION. IF
UNCONSCIOUS,GIVE OXYGEN. IF NOT BREATHING,GIVE CPR. EMPLOY FIRST
AID TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.
Unusual Fire/Explosio

n Hazard:WELDING ARCS & SPARKS CAN IGNITE
COMBUSTIBLE PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE &
PLACE IN APPROPRIATE DISPOSAL CONTAINER.

===== Handling and Storage =====

Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES.
MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES. AVOID ELECTRICAL SHOCK
BY MAINTAINING DRY WORK AREA.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN
CONFINED SPACES OR WHERE VENTILATION DOES NOT KEEP EXPOSURE BELOW
TLV.

Ventilation:LOCAL EXHAUST TO MAINTAIN BELOW TLV.

Protective Gloves:WELDER'S GLOVES.

Eye Protection:HELMET OR FACE SHIELD WITH FILTER LENS.

Other Protective Equipment:SUBSTANTIAL DARK CLOTH,ARM
PROTECTOR,APRON,HAT,SHOULDER PROTECTION.

Work Hygienic Practices:WASH HANDS THOROUGHLY BEF
ORE

EATING,SMOKING,USING SANITARY FACILITIES.

Supplemental Safety and Health

THE FUME LIMIT FOR CHROMIUM VI (0.05 MG/M*3) WILL BE REACHED BEFORE THE
GENERAL LIMIT OF 5MG/M*3 FOR FUMES IS REACHED.MONITOR FUMES FOR
CHROMIUM VI LEVEL.

===== Physical/Chemical Properties =====

HCC:N1

Appearance and Odor:WELDING RODS. 0.062 INCHES DIAMETER BY 36 INCHES
LONG

===== Stability and Reactivity Data =====

Stability Indicator/Materials

to Avoid: YES

Hazardous Decomposition Products: FUMES OF METALS & METAL
OXIDES, CO, CO*2, NO*2, O*3, FLUORIDES.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF FUMES, FLUX OR WELD GRINDING RESIDUE
IAW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.