

AMERON INC. -- AMERCOAT,78 RESIN BLACK -- 8010-00-997-2609

=====  
Product Identification  
=====

Product ID:AMERCOAT,78 RESIN BLACK

MSDS Date:01/01/1987

FSC:8010

NIIN:00-997-2609

Kit Part:Y

MSDS Number: BGCKN

=== Responsible Party ===

Company Name:AMERON INC.

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:JO831

=== Contractor Identification ===

Company Name:AMERON INC.

Addr

ess:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:JO831

Company Name:AMERON INTERNATIONAL PROTECTIVE COATINGS GROUP

Address:201 NORTH BERRY ST.

Box:City:BREA

State:CA

ZIP:92821

Country:US

Phone:714-529-1951

CAGE:55849

=====  
Composition/Information on Ingredients  
=====

Ingred Name:COAL TAR, CAS# 8007-45-2

CAS:8007-45-2

RTECS #:GF8600000

Fraction by Wt: 25%

ACGIH TLV:0.2 MG/CUM

Ingred Name:EPOXY RESIN, CAS# 65068-38-6

Fraction by Wt: 18%

ACGIH TLV:2 PPM(

SKIN)

Ingred Name:NAPHTHALENE (SARA III)

CAS:91-20-3

RTECS #:QJ0525000

Fraction by Wt: 7%

OSHA PEL:10 PPM/15 STEL

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 7%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL N-AMYL KETONE

CAS:110-43-0

RTECS #:MJ5075000

Fraction by Wt: 3%

OSHA PEL:100 PPM

ACGIH TLV:5

0 PPM; 9192

=====  
===== Hazards Identification =====

Effects of Overexposure:IRRIT:SKIN,MUC MEMB,EYE,RESP  
SYS.INHAL:HDCH,NAUS,DIZ,ASPHYXIA.SKIN SENSITIZATION-OTHER  
PRECAUTION.

=====  
===== First Aid Measures =====

First Aid:INHAL:FRESH AIR.GIVE O\*2,CPR.SKIN:WASH THOROUGHLY WITH SOAP  
AND WATER.EYE:FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR 15 MIN AND  
GET MEDICAL ATTENTION.LAUNDER CONTAMINATED CLOTHING BEFORE  
REUSE.

INGEST: DO NOT INDUCE VOMITING;CALL PHYSICIAN IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:121F,49C SCC

Lower Limits:1.1

Extinguishing Media:FOAM,CO\*2,DRY CHEMICAL

Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT,ELECTRICAL

EQUIPMENT,SPARKS AND OPEN FLAME.WEAR SELF-CONTAINED BREATHING APPARATUS

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION.USE

ABSORBENT

CLEANUP MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.STORE IN COOL,DRY,WELL-VENTILATED AREA.AVOID PROLONGED BREATHING OF VAPORS,SPRAY MIST,CONTACT W/ SKIN,EYES.

Other Precautions:WEAR PROTECTIVE BARRIER CREAM ON EXPOSED SKIN.OVEREXPOS:INHAL,INGEST,ABSORB THRU THE SKIN CAN BE HARMFUL.KIDNEY,LIVER DAMAGE MAY OCCUR.SKIN IRRITATION ACCENTUATED BY SUNLIGHT.

===== E

xposure Controls/Personal Protection =====

Ventilation:SUFFICIENT VENTILATION TO KEEP AIR CONTAMINANT CONC 1

Spec Gravity:1.43

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

Appearance and Odor:BLACK LIQUID,SOLVENT ODOR

Percent Volatiles by Volume:26

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:HEAT,OPEN FLAME,ARC OR

SPARKS.LIGHT;PHOTO

CHEMICALLY REACTIVE

Hazardous Decomposition Products:CO,CO\*2,NO\*X.BURN,WELD PRODUCE COAL  
TAR FUME,KEEP