

BORDEN INC., KRYLON DEPARTMENT -- KRYLON CRYSTAL CLEAR SPRAY 1303 (OLD FORM) --
8010-01-005-8577

===== Product Identification =====

Product ID:KRYLON CRYSTAL CLEAR SPRAY 1303 (OLD FORM)

MSDS Date:01/01/1987

FSC:8010

NIIN:01-005-8577

MSDS Number: BGCTN

=== Responsible Party ===

Company Name:BORDEN INC., KRYLON DEPARTMENT

Address:630 E WASHINGTON

Box:390

City:NORRISTOWN

State:PA

ZIP:19404

Country:U

S

CAGE:EO688

=== Contractor Identification ===

Company Name:BORDEN INC., KRYLON DEPT

Address:FORD & WASHINGTON ST

City:NORRISTOWN

State:PA

ZIP:19404

Country:US

Phone:(215) 278-2456

CAGE:EO688

Company Name:KRYLON PRODUCTS

Address:31500 SOLON ROAD

Box:City:SOLON

State:OH

ZIP:44139

Country:US

Phone:800-832-2541/216-566-2917

CAGE:87187

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 30%

OSHA PEL:200

PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 25%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:HEXANE (N-HEXANE)
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 19%
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 18%
OSHA
PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:NAPHTA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 2%
OSHA PEL:100 PPM

=====
===== Hazards Identification =====

Effects of Overexposure:DIZZY,CONFUSION,WEAKNESS

=====
===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.IF SPRAYED IN EYES,WASH WITH
WATER 15 MINUTES.

=====
===== Fire Fighting Measures =====

=====

Extinguishing Media:CO,CO2,FOAM,DRY CHEMICAL

Fire Fighting Procedures:WATER FOG TO COOL CAN TO PREVENT EXPOSURE TO HIGH TEMPS.

Unusual Fire/Explosion Hazard:FLAME FRONT IF SPRAYED DIRECTLY AT A OPEN FLAME.CAN MAY BURST WITH VIOLENCE WHEN EXPOSED TO HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION SOAK UP WITH ABSORBENT MATERIAL VENTILATE AREA.

===== Handling and Storage =====

=====

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURE OVER 120F.AVOID RADIATORS,STOVES,DIRECT SUNLIGHT OR OTHER HEAT SOURCE.HIGH TEMP MAY CAUSE BURSTING

Other Precautions:AVOID PUNCTURING IF SPRAY IS BURNED DO NOT BREATHE IRRITATING OR TOXIC FUMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED WITH ADEQUATE VENTILATION

Ventilation:SUPPLEMENT NATURAL VENTILATION AS NEEDED

Eye Protection:DESIRABLE

Supp

lemental Safety and Health

ACRYLIC ESTER RESIN COMPRISE 6.3% OF HAZARDOUS INGREDIENTS. MFR PHONE #:614-294-7447. PKG 16 OZ CAN FOR GRAPHIC ARTS.

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>1

Spec Gravity:1

Solubility in Water:SLIGHT

Percent Volatiles by Volume:94

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:BURNING SPRAY MAY PRODUCE TOXIC AND

IRRITATING COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:AVOID INCINERATION OF CAN OR USE ONLY A STRONG CLOSED INCINERATOR.DRIED LACQUER DISCARD AS NON-DANGEROUS TRASH TO BE BURIED OR BURNED IN ACCORDANCE WITH STATE,FEDERAL AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.