

STEPAN COMPANY -- STEPANFOAM G-506-R;PRODUCT #188318 -- 9330-01-006-5310

=====
Product Identification
=====

Product ID:STEPANFOAM G-506-R;PRODUCT #188318

MSDS Date:04/22/1987

FSC:9330

NIIN:01-006-5310

Kit Part:Y

MSDS Number: BGCTY

=== Responsible Party ===

Company Name:STEPAN COMPANY

Address:22 W. FRONTAGE RD

City:NORTHFIELD

State:IL

ZIP:60093-3407

Country:US

Info Phone Num:312-446-7500

Emergency

Phone Num:1-800-228-5635/312-446-7500

CAGE:87570

=== Contractor Identification ===

Company Name:STEPAN COMPANY

Address:EDENS EXPY WINNETKA RD

Box:City:WINNETKA

State:IL

ZIP:60093

Country:US

Phone:800-228-5635, CHEMTREC 800-424-9300

CAGE:87570

=====
Composition/Information on Ingredients
=====

Ingred Name:POLYOL RESIN, WATER BLOWN TYPE

Fraction by Wt: 100%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingesti

on: YES

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: ACUTE: IRRITATION TO EYE, SKIN AND
RESPIRATORY TRACT. CHRONIC; NO DATA AVAILABLE.

Effects of

Overexposure: EYES: PAIN, IRRITATION; SKIN; IRRITATION, INHALATION: IRRITATION OF NASAL PASSAGES; INGESTION: NOT SPECIFIED.

=====
First Aid Measures
=====

First Aid: EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER; SKIN: REMOVE
CONTAMINATED CLOTHING. WASH OFF WITH WATER; INHALATION: REMOVE TO
FRESH AIR GIVE CPR/OXYGEN IF NEEDED; INGESTION: SEE DOCTOR
IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method: PMCC

Flash Point: 230F, 110C

Extinguishing Media: WATER SPRAY, FOAM, CARBON DIOXIDE, DRY CHEMICALS

Fire Fighting Procedures: WEAR SCBA & FULL PROTECTIVE CLOTHING

Unusual Fire/Explosion Hazard: OPEN FLAME, SMOKING, ETC., MAY PRODUCE TOXIC
FUMES.

=====
Accidental Release Measures
=====

Spill Release

Procedures: SOAK UP WITH ABSORBENT. SHOVEL INTO WASTE
CONTAINER. FLUSH AREA WITH WATER. (SPILLED MATERIAL IS SLIPPERY)

Neutralizing Agent: NOT GIVEN.

=====
Handling and Storage
=====

Handling and Storage Precautions: STORE IN A DRY, WELL VENTILATED AREA AT
ABOUT 65-75F (18-25C)

Other Precautions: SMOKING, OPEN FLAMES OR OTHER IGNITION SOURCES MUST BE
PROHIBITED AT THE SITE OF ANY POLYISOCYANURATE APPLICATION
OPERATION. PROTECT FROM TORCHES/WELDING HEAT.

T.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: IF VAPORS ARE PRESENT, USE NIOSH/MSHA APPROVED
RESPIRATOR FOR ORGANIC VAPORS, AIR-LINE RESPIRATOR OR SCBA.

Ventilation: MECHANICAL (GENERAL) AND/OR LOCAL EXHAUST TO KEEP BELOW
TVL.

Protective Gloves: IMPERVIOUS

Eye Protection: FULL FACE SHIELD OR GOGGLES.

Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT

REPEATED OR PROLONGED CONTACT. EYE WASH STATION AND SAFETY SHOWER.

Work Hygiene

nic Practices:WASH THOROUGHLY AFTER HANDLING. REMOVE AND
LAUNDER CONTAMINATED CLOTHING.

Supplemental Safety and Health

KEY:N1. KIT CONSISTS OF 2 PARTS, FOR OTHER PARTS, SEE PNI B, SAME NSN.

===== Physical/Chemical Properties =====

HCC:T3

Boiling Pt:B.P. Text:>212F/100C

Vapor Density: