

FORCE CHEMICALS DIV, AMERICAN SOLDER&FLUX CO,INC. -- 8 CORROSIVE, MIL-F-14256D, TY RMA -- 3439-01-007-5494

===== Product Identification =====

Product ID:8 CORROSIVE, MIL-F-14256D, TY RMA

MSDS Date:01/01/1985

FSC:3439

NIIN:01-007-5494

MSDS Number: BGCWH

=== Responsible Party ===

Company Name:FORCE CHEMICALS DIV, AMERICAN SOLDER&FLUX CO,INC.

Address:INDUSTRIAL BLVD

City:PAOLI

State:PA

ZIP:19301

Cou

ntry:US

CAGE:DO821

=== Contractor Identification ===

Company Name:AMERICAN SOLDER AND FLUX CO INC FORCE CHEMICAL DIV

Address:28 INDUSTRIAL BLVD

Box:City:PAOLI

State:PA

ZIP:19301

Country:US

Phone:800-424-9300

CAGE:70540

Company Name:FORCE CHEMICALS DIVISION-AMERICAN SOLDER & FLUX CO

Address:28 INDUSTRIAL BLVD.

City:PAOLI

State:PA

ZIP:19301

Country:US

Phone:215647-3575

CAGE:DO821

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL

Fraction by Wt: 83

%.
ACGIH TLV:S, 400 PPM

===== Hazards Identification =====

Effects of Overexposure:SLIGHT SKIN IRRITATION, HEADACHE OR GIDDINESS.

===== First Aid Measures =====

First Aid:INHAL:MOVE TO FRESH AIR. EYES:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 MIN. SKIN:FLUSH W/PLENTY OF WATER. INGEST:CALL MD, IF CONSCIOUS INDUCE VOMITNG.

===== Fire Fighting Measures =====

Flash Point:83F COC
(55F TCC
Lower Limits:2.0
Upper Limits:12.
Extinguishing Media:CO*2, DRY CHEMICAL, ALCOHOL FOAM
Fire Fighting Procedures:SIL.OF BURNING LIQ.W/VOL.OF WATER.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. AVOID INHALATION OF FUMES OR MIST

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS AT AMBIENT CONDITIONS.
Other Precautions:A
VOID CONTACT WITH SKIN. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE FOR NORMAL USE.
Ventilation:LOCAL-MAINTAIN ADEQUATE VENTILATION.
Protective Gloves:RUBBER GLOVES
Eye Protection:CHEM.SFTY GOGGLES
Supplemental Safety and Health
SPECIFIC GRAVITY IS GIVEN AT 72F

===== Physical/Chemical Properties =====

HCC:F4
NRC/State Lic Num:NA
Boiling Pt:B.P. Text:194F
Vapor Pres:28
Vapor Den

sity:1.7
Spec Gravity:0.823
Evaporation Rate & Reference:>1 BUTYL ACETATE
Solubility in Water:SLIGHT
Appearance and Odor:COLOR #1 GARDNER SCALE, ALCOHOL ODOR.
Percent Volatiles by Volume:84.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:FLUSH WITH WATER TO CHEMICAL SEWER OR CONTROLLED
BURNING, IN ACCORDANCE WITH FEDERAL, STATE AND
LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.