

GOULD INC.INST.SYS. DIV(DIST), PHILIP A. HUNT(MFR) -- 270613, GOULD 4800 TONER --
6850-01-008-3781

===== Product Identification =====

Product ID:270613, GOULD 4800 TONER

MSDS Date:01/01/1985

FSC:6850

NIIN:01-008-3781

MSDS Number: BGCYG

=== Responsible Party ===

Company Name:GOULD INC.INST.SYS. DIV(DIST), PHILIP A. HUNT(MFR)

Address:10 GOULD CENTER

City:ROLLING MEADOWS

State:IL

ZIP:60008-4043

Coun

try:US

Emergency Phone Num:NONE

CAGE:MO497

=== Contractor Identification ===

Company Name:GOULD INC INST SYS DIV

Address:10 GOULD CENTER

Box:City:ROLLING MEADOWS

State:IL

ZIP:60008-4043

Country:US

Phone:708-640-4135

CAGE:1L156

Company Name:GOULD INC.INST.SYS. DIV(DIST), PHILIP A. HUNT(MFR)

Address:10 GOULD CENTER

Box:City:ROLLING MEADOWS

State:IL

ZIP:60008-4043

Country:US

CAGE:MO497

===== Composition/Information on Ingredients =====

Ingred Name:MIXED ISODECANES

Fraction by Wt

: 99.0%
ACGIH TLV:300 PPM

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION: HEADACHE,NAUSEA,UPSET
STOMACH;POSSIBLE IRRITATION,MILD DEPRESSION,RESPIRATORY IRRITATION

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE FROM SOLVENT-LADEN AREA TO FRESH AIR AREA.
ACCIDENTAL INGESTION: CALL DOCTOR IMMEDIATELY; DO NOT INDUCE
VOMITING. IN EYES: FLUSH THOROUGHLY WITH CLEAN,WARM WATER FOR
UP TO
15 MINUTE S. IF IRRITATION PERSISTS, CALL DOCTOR.

=====
Fire Fighting Measures
=====

Flash Point:125-128F TCC
Lower Limits:0.7
Upper Limits:6.5
Extinguishing Media:FOAM-TYPE EXTINGUISHERS-SUPERIOR TO CO*2
EXTINGUISHERS.
Fire Fighting Procedures:AVOID WATER--IT TENDS TO SPREAD HYDROCARBON
FIRES.
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:IF AMOUNT IS SMALL (
UNDER 1 PINT) ALLOW TO
EVAPORATE-INCREASING AIR CIRCULATION IF POSSIBLE; AVOID ANY SPARKS
& OPEN FLAMES. IF AMOUNT IS LARGE, TRY TO CONTAIN & SOP UP INTO A
CONTAINER WHICH CAN BE C LOSED. AVOID BREATHING VAPORS.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID STORAGE NEAR HEAT, SPARKS, OR
OPEN FLAMES.
Other Precautions:AVOID USE IN A SMALL CLOSED ROOM OR CONFINED AREA
WITH POOR AIR CIRCULATION. WASH SKIN WITH SOAP &

WATER AFTER
CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED
Ventilation:LOCAL EXHAUST & MECHANICAL.
Protective Gloves:NONE
Eye Protection:NONE
Other Protective Equipment:NONE
Supplemental Safety and Health
ITEM IS PART OF PACKAGE-84606-01 TONER KIT FOR THE GOULD 4800
ELECTROSTATIC PRINTER/PLOTTER. SEE ADDITIONAL DATA FIELD FOR MORE
INFORMATION.

===== Physical/Chemical Properties =====

HCC:
F4
Boiling Pt:B.P. Text:350-375F
Vapor Pres:34
Vapor Density:5.0
Spec Gravity:0.755
Evaporation Rate & Reference:0.1(N-BUTYL ACETAT
Solubility in Water:0.01%
Appearance and Odor:BLACK, MOBILE LIQUID; FAINT HYDROCARBON ODOR.
Percent Volatiles by Volume:99+

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS LIKE CHROMIC ACID,LIQUID CHLORINE,OR CONC OX
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:LARGE CONTAINERS OF WASTE MUST BE HANDLED BY
PERSONS OR FIRMS WITH FACILITIES FOR DISPOSAL (E.G., CONTROLLED
BURNING). DO NOT DISCHARGE INTO SEWER, STREAMS, OR WATERWAYS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this informat

ion to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.