View NSN Online: https://aerobasegroup.com/nsn/6850-01-011-2351

SIFCO SELECTIVE PLATING -- 30205506 -- 6850-01-011-2351

Product ID:30205506 MSDS Date:11/01/1985 FSC:6850 NIIN:01-011-2351 MSDS Number: BGDDD === Responsible Party === Company Name:SIFCO SELECTIVE PLATING Address:5708 SCHAAF ROAD City:CLEVELAND State:OH ZIP:44131 Country:US Info Phone Num:261-881-8600 Emergency Phone Num:216-881-8600 CAGE:DO645 === Contractor Id entification === Company Name: SIFCO SELECTIVE PLATING DIV OF SIFCO INDUSTRIES INC. Address:5708 SCHAAF ROAD Box:City:CLEVELAND State:OH ZIP:44131-1394 Country:US Phone:216-524-0099/ FAX: -6331 CAGE:11924 Company Name: SIFCO SELECTIVE PLATING, DIV OF SIFCO INDUSTRIES INC Address:5708 SCHAAF ROAD City:CLEVELAND State:OH ZIP:44131-1394 Country:US Phone:216-524-0099 CAGE:DO645

Ingred Name:COPPER FLUOROBORATE CAS:38465-60-0 ACGI Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:EROSION OF TEETH,JAW NECROSIS,BRONCHIAL IRRITATION,CHRONIC COUGH,BRONCHIAL PNEUMONIA,ASTHMA,GASTROINTESTINAL DISTURBANCES,LIVER & KIDNEY DAMAGE,FLUOROSIS Effects of Overexposure:EYE-PAIN,TEARING,PHOTOPHOBIA,CONJUNCTIVAL EDEMA;CORNEAL DAM/DESTRUCT. SKIN0-SEVERE PAIN;BURNS-SLOW HEALING,SCARS;S ENSITIZATION,DERMATITIS;CONJUNTIVAE. INHAL-IRRITAT TO LUNGS/RESPIR TRACT;COUGH,CHOK,HE ADACHE,DIZZ,CYANOSIS,HEMOPTYSIS. INGEST-SEVERE BURNING PAIN-MOUTH,PHARYNX,ABDO;VOMIT,GASTRIC PERFORATION;CAN BE FATAL.

First Aid:EYE-FLUSH W/WATER 15 MIN;CONSULT DOC. SKIN-IMMED FLUSH W/WATER;REMV CONTAM CLOTH & SHOES;OPEN ALL BLISHERS;WASH;COAT BURN W/MGO/WATER PASTE W/20% GLYCERIN;DO NOT USE OILY OINTMT;SEE PHYS. I

NHAL-GET TO FRESH AIR;CALL PHYSICIAN. INGEST-DO NOT INDUCE VOMIT;IMMED GIVE LGE AMT WATER OR MILK;IF VOMIT PERSISTENT,GIVE FLUIDS REPEATEDLY;CALL PHYSICIAN.

Flash Point:NONE Lower Limits:NONE Upper Limits:NONE Extinguishing Media:ALL Fire Fighting Procedures:WEAR FACE SHIELD/GOGGLES,IMPERVIOUS GLOVES,BOOTS,PROTECT CLOTH. NIOSH/MSHA APPRD RESPIR PROTECTION AS REQD. Unusual Fire/Explosion Hazard:EXCESSIVE HEAT MAY CAUSE CONTNRS TO

BURST. LIQUID MAY LIBERATE CORROSIVE HYDROGEN FLUORIDE GAS.

Spill Release Procedures:COVER W/SODIUM BICARB OR SODA ASH-SLAKED LIME/50-50 MIX/. MIX & MAKE SLURRY. CAREFULLY MOP UP OR VACUUM SPILL & RINSE WATER INTO SUITABLE PLASTIC CONTNR. SHIP TO LOCAL TREATMENT/DISPOSAL FACILITY. FLU SH SPILL AREA W/PLENTY WATER. Neutralizing Agent:SEE ABOVE

================== Handling and Storage ==

Handling and Storage Precautions:DO NOT GET IN EYES,ON SKIN/CLOTHING.DO NOT BREATHE VAPOR,MISTS OR GAS.USE W/ADEQUATE VENT.WASH THOROUGHLY AFTER HANDLING.PROTECT FROM PHYS DAMAGE.
Other Precautions:KEEP CONTNR TIGHTLY CLOSED IN UPRIGHT POSITION. STORE AT 50-90F AWAY FM INCOMPATABLE MATLS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH/MSHA APPROVED Ventilation:LOCAL EXHAUST REQD Protective Gloves:NEOPRENE,VINYL

Eye Protection:FACE SHIELD,CHEM GOGGLES Other Protective Equipment:IMPERV BOOTS,APRON,PROTECT CLOTH AS REQD. EYE FOUNTAIN,SAFETY SHOWER,WASHING FACILITIES NEAR WORK AREA. Supplemental Safety and Health

HCC:C1 Boiling Pt:B.P. Text:>212F/100C Spec Gravity:1.397-1.417 Evaporation Rate & amp; Reference: