

ASHLAND CHEMICAL CO -- 140 SOLVENT NONEXEMPT -- 6850-01-016-3482

=====
Product Identification
=====

Product ID:140 SOLVENT NONEXEMPT
MSDS Date:01/01/1985
FSC:6850
NIIN:01-016-3482
MSDS Number: BGDQK
=== Responsible Party ===
Company Name:ASHLAND CHEMICAL CO
Address:3849 FISHER RD
City:COLUMBUS
State:OH
ZIP:43228-1017
Country:US
CAGE:7L600

==== Contractor Identification ====
Company Name:ASHLAND CHEMICAL CO DIV OF ASHLAND OIL INC
Address:3849 FISHER RD
Box:2219
City:COLUMBUS
State:OH
ZIP:43216
Country:US
Phone:614-790-3333 / 800-325-3751
CAGE:7L600

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC HYDROCARBON
Fraction by Wt: 100%
ACGIH TLV:350 MG/CUM

=====
Hazards Identification
=====

Effects of Overexposure:SEVERE SKIN & EYE
IRRITATION;DIZZINESS,FATIGUE,NAUSEA,HEADACHE,POSSIBLE ASPHYXIATION

=====

=====
First Aid Measures
=====

First Aid:SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER.INHAL:
REMOVE TO RESH AIR,GIVE ARTIFICIAL RESPIRATION IF
NECESSARY.INGESTION: DO NOT INDUCE VOMITING. KEEP PERSON WARM &
QUIET & GET MEDICAL ATTENTIO N.

=====
Fire Fighting Measures
=====

Flash Point:138F (59C)(CC)

Lower Limits:1.0

Extinguishing Media:REGULAR FOAM, CARBON DIOXIDE OR DRY CHEMICAL

Fire Fighting Procedures:SELF-CONTAINED

BREATHING APPARATUS WITH FULL

FACE PIECE

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR; MAY TRAVEL ALONG
FLOOR & IGNITE BY HEAT, FLAMES & OTHER IGNITION SOURCES.

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. WEAR
PROTECTIVE CLOTHING DIKE AREA OF SPILL, PUMP LIQUID TO SALVAGE
TANK. REMAINING LIQUID MAY BE ABSORBED WITH SAND,CLAY, ETC &
SHOVELED INTO CONTAINERS. PREVENT RU NOFF TO SEWER
S, STREAMS &
OTHER BODIES OF WATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:EMPTY CONTAINERS RETAIN PRODUCT
RESIDUES & MUST BE TREATED ACCORDINGLY.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS W/FULL FACE
PIECE SUFFICIENT TO

Ventilation:MAINTAIN EXPOSURE LEVEL BELOW TLV

Protective Gloves:BUANA-N

Eye Protection:GOGGLES

Other Protective Equip

ment:TO PREVENT PROLONGED/REPEATED EXPOSURE -
IMPERVIOUS CLOTHIN

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:355F(179C)

Vapor Pres:0

Vapor Density:5.4

Spec Gravity:0.780

Evaporation Rate & Reference:151 (ETHER =1)

Appearance and Odor:COLORLESS TO YELLOW CLEAR LIQUID

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoi

d:YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:CARBON DIOXIDE & CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION OR DEPOSIT IN A POSTED TOXIC
SUBSTANCE LANDFILL IN ACCORDANCE WITH LOCAL, STATE, & FEDERAL
REGULATION

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in

no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.