

HOHMAN PLATING & MFG.,INC. -- SURF-KOTE LOB-1800G, CLASS A -- 9150-01-020-3610

=====
Product Identification
=====

Product ID:SURF-KOTE LOB-1800G, CLASS A

MSDS Date:01/01/1987

FSC:9150

NIIN:01-020-3610

MSDS Number: BGDZC

=== Responsible Party ===

Company Name:HOHMAN PLATING & MFG.,INC.

Emergency Phone Num:(513) 228-2191

CAGE:DO354

=== Contractor Identification ===

Company Name:HOHMAN PLATING & MFG
INC.

Address:814 HILLROSE AVE.

Box:City:DAYTON

State:OH

ZIP:45404-1132

Phone:513-228-2191

CAGE:DO354

Company Name:HOHMAN PLATING AND MFG INC

Address:814 HILLROSE AVE

Box:City:DAYTON

State:OH

ZIP:45404-1132

Country:US

Phone:937-228-2191

CAGE:01094

=====
Composition/Information on Ingredients
=====

Ingred Name:GRAPHITE (CAS #7782-42-5)

RTECS #:VV7780000

Fraction by Wt: 15.8%

ACGIH TLV:10 PPM (DUST)

Ingred Name:SODIUM SILICATE (CAS #1344-09-8)

CAS:6834-92-0

RTECS #:VV9275000

F

raction by Wt: 31.8%

Ingred Name:WATER (CAS #7732-18-5)

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 51.4%

Ingred Name:SOLIDS, HAZARD UNKNOWN, UNIDENTIFIED

Fraction by Wt: 1%

=====
Hazards Identification
=====

Effects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.

=====
First Aid Measures
=====

First Aid:INGEST:RMV FM EXPOSURE.DILUTE W/WATER TO WHICH VINEGAR/LEMON JUICE HAS BEEN ADDE

D.GET MED ATTN;SKIN:FLUSH W/PLENTY OF WATER;EYES:FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MIN.IF IRRIT OCCURS/PERSISTS,GE T MED ATTN;INHAL OF DUST:REMOVE FM EXPOSURE.

=====
Fire Fighting Measures
=====

Flash Point:NONE

Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.

Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

=====
Acciden
tal Release Measures
=====

Spill Release Procedures:USE APPROPRIATE SAFETY EQUIPMENTS DURING CLEAN UP.CONTAIN THE SPILL.SRAPE UP & RECLAIM OR ABSORB & DISPOSE OF IN A WASTE CONTAINER.WASH THE AREA WITH WATER AND DETERGENT.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precauti

ons:LAUNDER CLOTHES BEFORE REUSE.DO NOT EAT OR SMOKE
WHERE THIS MATL IS PRESENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF NEEDED,USE NIOSH APPROVED EQUIPMENT.
Ventilation:LOCAL EXHAUST PREFERRED,MECHANICAL EXHAUST ACEPTABLE.
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES
Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE
WASH STATION
Supplemental Safety and Health
MSDS FM HOHMAN PLATING CO DATED: 10/85.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:212F,100C
Vapor Pres:17
Spec Gravity:>1.0
Solubility in Water:APPRECIABLE
Appearance and Odor:BLUE-BLACK LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
ALKALI METALS
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:CO,CO*2

===== Disposal Considerations =====

Waste Disposal Methods:
NEUTRALIZE WASTE IF NEEDED & DISPOSE OF I/A/W
APPLICABLE FED,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify an

d

assume responsibility for the suitability of this information to their particular situation.