View NSN Online: https://aerobasegroup.com/nsn/6750-01-022-8410

Product ID:106 5895, FLEXCOLR BLCH II, PART A(POST 1987) MSDS Date:01/29/1987 FSC:6750 NIIN:01-022-8410 Kit Part:Y MSDS Number: BGFDP === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone N um:716-477-3194 FOR MSDS : 242-2424 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 60-65%

Ingred Name:AMMONIUM BROMIDE CAS:12124-97-9 RTECS #:BO9170000 Fraction by Wt: 20-25%

Ingred Name:AMMONIUM ACETATE (SARA III) CAS:631-61-8 RTECS #:AF3675000 Fraction by Wt: 10-15% EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ACETIC ACID (SARA III) CAS:64-19-7 RTECS #:AF1225000 Fraction by Wt: 1-5% OSHA PEL:10 PPM ACGIH TLV:10 PPM/15 STEL; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYES: IRRITATING;SKIN:LOW HAZARD;INHALATION:LOW HAZARD Explanation of Carcinogenicity:NOT LISTED Effects of Overexposure:SEE HEALTH HAZARDS Medical Cond Aggravated by Exposure:NONE NOTED BY MANUFACTURER

First Aid:EYES:FLUSH WITH PLENTY OF WATER; SKIN: FLUSH WITH SOAP & WATER; INHALATION: REMOVE TO FRESH AIR; INGESTION: DRINK ONE OR TWO GLASSES OF WATER, SEEK MEDICAL ATTENTION.

=================== Fire Fighting Measu

Flash Point:NONE

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE, ALCOHOL FOAM

Fire Fighting Procedures:WEAR SELF-CONTAINED & PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN & EYES.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS

Spill Release Procedures: FLUSH TO SEWER WITH LARGE AMOUNTS OF WATER. FOLLOW WIT

## H SECONDARY WASTE WATER TREATMENT

Handling and Storage Precautions: KEEP FROM CONTACT WITH OXIDIZING MATERIALS.

======= Exposure Controls/Personal Protection ==========

Ventilation:GOOD GENERAL VENTILATION Protective Gloves:AS REQUIRED Eye Protection:SAFETY GLASSES Work Hygienic Practices:STANDARD HYGENIC PRACTICES Supplemental Safety and Health THIS CAT #106-5895 IS REPLACEMENT FOR 190-1685 WHICH WAS DISCONTIN UED IN MAY,1987. THIS NEW CATALOG CONSISTS OF 2-PART A,& B. THIS IS PART-A. FOR PART-B, SEE P/N IND G. PART-A IS NOT REGULATED & PT-B IS CORROSIVE LIQUID. PART A,FLEXICOLOR BLEACH II SOLUTION NO:5308;

KEY1=N1.

## HCC:N1

Boiling Pt:B.P. Text:>212F,>100C Vapor Pres:18 Vapor Density:0.6 Spec Gravity:1.148 pH:5.84 Evaporation Rate & amp; Reference:0.4(BU AC=1) Solubility in Water:COMPLETE Appearance and Odor:COLORLES S CLEAR SOLUTION;SLIGHT ACETIC ODOR Percent Volatiles by Volume:65

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:HEAT,OPEN FLAMES Hazardous Decomposition Products:AMONIA AND OXIDES OF CARBON IN COMBUSTION.

Waste Disposal Methods:DISCHARGE,TREATMENT,OR DISPOSAL MAY BE SUBJECT TO FEDERAL,STATE OR LOCAL LAWS. Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situati on.