

LIGHTALARMS ELECTRONICS CORP (GRAYBAR DISTR-1B241) -- L-3 (SEE ADDTL DATA) --  
6140-01-024-8980

===== Product Identification =====

Product ID:L-3 (SEE ADDTL DATA)

MSDS Date:01/01/1985

FSC:6140

NIIN:01-024-8980

MSDS Number: BGFLX

=== Responsible Party ===

Company Name:LIGHTALARMS ELECTRONICS CORP (GRAYBAR DISTR-1B241)

Address:1510 TOMLYNN ST

City:RICHMOND

State:VA

ZIP:23230-3313

Country:US

CAGE:027

20

=== Contractor Identification ===

Company Name:GRAYBAR ELECTRIC CO INC

Address:1510 TOMLYNN ST

Box:City:RICHMOND

State:VA

ZIP:23230-3313

Country:US

Phone:804-359-1381

CAGE:1B241

Company Name:LIGHTALARMS ELECTRONICS CORP

Address:1170 ATLANTIC AVENUE

Box:City:BALDWIN

State:NY

ZIP:11510-4205

Country:US

Phone:516-379-1000

CAGE:02720

===== Composition/Information on Ingredients =====

Ingred Name:SULFURIC ACID (SARA III)

CAS:7664-93-9

RTECS #:WS5600000

Fraction by Wt: 31%

OSHA

PEL:1 MG/M3  
ACGIH TLV:1 MG/M3; 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:WATER  
CAS:7732-18-5  
RTECS #:ZC0110000  
Fraction by Wt: 69%

=====  
Hazards Identification  
=====

Effects of Overexposure:H\*2504 IS CORROSIVE. IT WILL CAUSE FIRST DEGREE SKIN BURNS.

=====  
First Aid Measures  
=====

First Aid:FLOOD WITH FRESH WATER.SEEK MEDICAL ASSISTANCE.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Fire Fighting Procedures:NONE  
Unusual Fire/Explosion Hazard:BATTERY MAY OUTGAS HYDROGEN GAS AT ELEVATED TEMPERATURE OR DURING OVERCHARGE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:FLOOD WITH WATER TO DILUTE - COVER WITH SODIUM CARBONATE OR AN EQUAL MIXTURE OF SODA ASH & SLAKED LIME. AFTER MIXING, ADD WATER IF NECESSARY TO FORM A SLURRY.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:WEAR RUBBER GLOVES, GOGGLES AND APPROPRIATE PROTECTIVE CLOTHING WHEN HANDLING WET BATTERIES.

=====  
Exposure Controls/Personal Protection  
=====

Ventilation:ADEQUATE  
Protective Gloves:RUBBER  
Eye Protection:GOGGLES OR SAFETY GLASSES  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:C1  
Spec Gravity:1.220  
Solubility in Water:COMPLETE  
Appearance and Odor:CLEAR - SULFUROUS ODOR

=====

=== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: HYDROGEN GENERATED, WHEN ITEM CONNECTED TO BATTERY CHARGER.

===== Disposal Considerations =====

Waste Disposal Methods: ADD SLOWLY TO A LARGE AMT OF SOLUTION OF SODA ASH & SLAKED LIME BY STIRRING. DISCHARGE SOLUTION WITH LARGE AMT OF WATER INTO A LINED SINK OF PROTECTIVE MATTING, & FILLED WITH CHIPPED MARBLE.

Disclai

mer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.