

TELECOMMUNICATION DEVICES,INC. -- NICKEL CADMIUM BATTERY -- 6140-01-025-2620

=====  
Product Identification  
=====

Product ID:NICKEL CADMIUM BATTERY

MSDS Date:01/01/1985

FSC:6140

NIIN:01-025-2620

MSDS Number: BGFNP

=== Responsible Party ===

Company Name:TELECOMMUNICATION DEVICES,INC.

Address:2320 WISCONSIN AVE

City:DOWNERS GROVE

State:IL

ZIP:60515-4091

Country:US

Emergency Phone Num:630-971-3460

CAG

E:55150

=== Contractor Identification ===

Company Name:TELECOMMUNICATION DEVICES INC

Address:2320 WISCONSIN AVE

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-4091

Country:US

Phone:708-971-3460

CAGE:55150

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POTASSIUM HYDROXIDE (SARA III)

CAS:1310-58-3

RTECS #:TT2100000

Fraction by Wt: >20%

OSHA PEL:C, 2 MG/M3

ACGIH TLV:C 2 MG/M3; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====  
Hazards Identificati  
=====

on =====

Effects of Overexposure:SORE THROAT,COUGHING,SHORTNESS OF BREATH,LABORED BREATHING,CORROSIVE TO SKIN,SKIN BURNS,DIARRHEA.

===== First Aid Measures =====

First Aid:INHALATION:FRESH AIR,REST & CARRY TO HOSPITAL.SKIN:REMOVE CONTAMINATED CLOTHES,RINSE SKIN W/PLENTY OF WATER.EYES:FIRST RINSE W/PLENTY OF WATER,THEN CARRY TO DOCTOR,IF NECESSARY.INGEST:RINSE MOUTH,GIVE PLENTY OF WATER TO DRINK & CARRY TO HOSPITAL.

===== Fire Fighting Measures =====

Extinguishing Media:LARGE VOL.OF H\*2O,DO NOT SPLASH SOLUTION(IN CASE OF FIRE).

Fire Fighting Procedures:COOL EXPOSED CONTAINERS W/H\*2O

Unusual Fire/Explosion Hazard:FLAMM.GAS MAY BE PRODUCED ON CONTACT W/METALS.MAY CAUSE FIRE ON CONTACT W/MOISTURE & COMBUSTIBLES.

===== Accidental Release Measures =====

Spill Release Procedures:DO NOT TOUCH SPILLED MATERIAL.EVACUATE UNPROTECTED PERSONS.WEAR P ROTECTIVE EQUIP.STOP LEAK.SM SPL:ABS W/ABSORBENT & PUT IN APPD CONTRS.LG SPL:CONTAIN W/DIKE & TRANSFER TO APPD CONTRS.PROVIDE VENTILATI ON.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED.STORE IN COOL,DRY,WELL VENTILATED AREA;PROTECT CONTAINERS FROM PHYSICAL DAMAGE & AVOID CONTACT W/SKIN.AVOID CONT W/ACID

Other Precautions:AVOID CONTACT W/CHLORINE DIOXIDE,NITROBENZENE,NITROGEN TRICHLORI DE,2,4,6-TRINITROTOLUENE.REMOVE & WASH CONTAMINATED CLOTHING.MAINTAIN STRICT HYGIENE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS.

Ventilation:LOCAL EXHAUST IS PREFERRED.

Protective Gloves:RUBBER

Eye Protection:SAFETY GOGGLES

Supplemental Safety and Health ITEM IS A NON-SPILLABLE BATTERY.

===== Physical/Chemical Properties =====

HCC:B1

Boiling Pt:B.P. Text:VERY HIGH

Vapor Pre

s:UNK  
Spec Gravity:2.04  
Solubility in Water:APPRECIABLE  
Appearance and Odor:COLORLESS LIQUID,ODORLESS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AL,SN,PB,ZN,ACIDS,HALOGENATED HYDROCARBONS,GLASS  
Hazardous Decomposition Products:PRODUCE FLAMMABLE HYDROGEN GAS  
CONTACT W/AL,ZN,SN,PB.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL.HANDLE &  
DISPOSE IN FULL COMPLIANCE W/ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to ve  
rify and  
assume responsibility for the suitability of this information to their  
particular situation.