

METCO INC. -- METCO ALUMINUM WIRE (SF & AW) -- 3439-01-028-8148

=====
Product Identification
=====

Product ID:METCO ALUMINUM WIRE (SF & AW)

MSDS Date:01/01/1987

FSC:3439

NIIN:01-028-8148

MSDS Number: BGFTL

=== Responsible Party ===

Company Name:METCO INC.

Emergency Phone Num:516 334 1300

CAGE:EO530

=== Contractor Identification ===

Company Name:METCO INC, SUB OF THE PERKIN-ELMER CORP

Address:1101

PROSPECT AVENUE

Box:City:WESTBURY

State:NY

ZIP:11590-2724

Country:US

Phone:516-334-1300

CAGE:39918

Company Name:METCO INC.

CAGE:EO530

=====
Composition/Information on Ingredients
=====

Ingred Name:ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

OSHA PEL:15MG/M3 DUST/5 FUME

ACGIH TLV:10MG/M3 DUST; 9192

=====
Hazards Identification
=====

Effects of Overexposure:RESPIRATORY IRRITATION,POSSIBLE NAUSEA.
POSSIBLE SKIN IRRITATION.

=====

===== First Aid Measures =====

First Aid:EXPOSE TO FRESH AIR. IF SKIN IRRITATION OCCURS,WASH W/SOAP & H*20.IF IRRITATION PERSISTS,CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE CLASS D EXTINGUISHING AGENTS OR DRY SAND ON FIRES.

Fire Fighting Procedures:TREAT AS A METALLIC FIRE.

Unusual Fire/Explosion Hazard:MODERATE FIRE HAZARD IN THE FORM OF DUST WHEN EXPOSED TO FLAME.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT PERMIT SPRAY DUST TO ENTER EYES, MOUTH, CUTS, SCRATCHES OR OPEN WOUNDS.

Other Precautions:FOLLOWING LENS SHADES RECOMMENDED FOR PROCESS INDICATED:COMBUSTION SPRAYING SHADE #5,ARC SPRAYING SHADE #9.EAR PROT MUST BE WORN WHEN OPERATOR IS SUBJECT TO EXCESS NOISE LVL.SEE OSHA REQRMENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection

NIOSH/MSHA APVD RESPIRATOR FOR DUST/FUMES/MISTS DURING THERMAL SPRAY

Ventilation:LOCAL EXHAUST-CREATE AIR VELOCITY OF 200 FPM.(SEE SUPP DATA)

Protective Gloves:ALUMINIZED

Eye Protection:RECM WHEN HANDLING WIRE

Other Protective Equipment:RECM ALUMINIZED GLOVES,ALUMINIZED APRON DURING ARC SPRAYING.

Supplemental Safety and Health

DESCRIPTN:ALUMINUM ALLOY WIRE USED FOR THERML SPRAY PROCESS.MELT PT:1190-1215F. VENTILATN:GENERL MECHANICL-ADEQ EXHAUST SYS REQ TO AVOID EFFECT OF DUST,FUME,MIST POSS GENERATD BY THERMLSPRAY.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:2.70

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WIRE;NO ODOR

Percent Volatiles by Volume:0

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL & FEDERAL REGULATIONS. WASTE DISPOSAL MUST BE IAW FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies)

:
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.