

SOUTHWEST PETRO-CHEM -- SB 836 9157 (SAE GRADE 75W) -- 9150-01-035-5391

=====  
Product Identification  
=====

Product ID:SB 836 9157 (SAE GRADE 75W)

MSDS Date:01/01/1985

FSC:9150

NIIN:01-035-5391

MSDS Number: BGGJM

=== Responsible Party ===

Company Name:SOUTHWEST PETRO-CHEM

Emergency Phone Num:913-782-5800

CAGE:70878

=== Contractor Identification ===

Company Name:EXXON CO USA-SOUTHWEST GREASE BUSINE  
SS UNIT

Address:1400 S HARRISON

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:913-656-3701/800-424-9300(CHEMTREC)

CAGE:70878

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM HYDROCARBON

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRITANT TO SKIN & EYES W/PROLONGED EXPOSURE.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH W/WATER FOR 15 MINUTES. C

ALL PHYSICIAN. SKIN:

WASH THOROUGHLY WITH SOAP AND WATER. INGESTION: CALL PHYSICIAN  
IMMEDIATELY.

=====  
Fire Fighting Measures  
=====

Flash Point:400F, 204C, COC

Extinguishing Media:DRY CHEMICAL, FOAM, SAND, EARTH, WATERFOG, CO\*2.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:DENSE SMOKE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:TRANSFER BULK OF MATERIA

L INTO ANOTHER

CONTAINER. ABSORB REMAINING MATERIAL WITH PROPER ABSORBENT SUCH AS SAND, EARTH, VERMICULITE. SWEEP UP AND DISPOSE AS SOLID WASTE.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:MFR RECOMMENDS NONE

Ventilation:MFR RECOMMENDS NONE

Protective Gloves:RUBBER

Eye Protection:FULL FACE SHIELD/SFTY GOG

Other Prot

ective Equipment:GLOVES: ALSO PLASTIC OIL RESISTANT.

Supplemental Safety and Health

SPEC: MIL-L-2105C. CONTAINER: 5 GAL CAN.

=====  
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:149C, 300F

Spec Gravity:0.936

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER LIQUID WITH MINERAL OIL ODOR.

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS: CHROMIC ACID, H\*2O\*2,  
BROMINE

Hazardous Decomposition Products:CO & CO\*2

=====  
===== Disposal Considerations =====

Waste Disposal Methods:WASTE DISPOSAL METHOD MUST BE IAW FEDERAL, STATE  
AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.