

SOUTHWEST PETRO-CHEM -- SB 836 9213(FORMERLY,88146) -- 9150-01-035-5392

=====  
Product Identification  
=====

Product ID:SB 836 9213(FORMERLY,88146)

MSDS Date:01/01/1985

FSC:9150

NIIN:01-035-5392

MSDS Number: BGGKK

=== Responsible Party ===

Company Name:SOUTHWEST PETRO-CHEM

Emergency Phone Num:913-782-5800

CAGE:70878

=== Contractor Identification ===

Company Name:EXXON CO USA-SOUTHWEST GREASE BUSINE  
SS UNIT

Address:1400 S HARRISON

Box:1974

City:OLATHE

State:KS

ZIP:66061

Country:US

Phone:913-656-3701/800-424-9300(CHEMTREC)

CAGE:70878

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM HYDROCARBON

=====  
Hazards Identification  
=====

Effects of Overexposure:IRRITANT TO SKIN & EYES W/ PROLONGED CONTACT.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH W/WATER FOR 15 MIN. CALL

PHYSICIAN. SKIN: WASH

THOROUGHLY WITH SOAP AND WATER. INGESTION: CALL PHYSICIAN  
IMMEDIATELY.

=====  
Fire Fighting Measures  
=====

Flash Point:400F, 204C, COC

Extinguishing Media:DRY CHEMICAL, FOAM, SAND, EARTH, WATERFOG, CO\*2.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:DENSE SMOKE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:TRANSFER BULK OF MATERIAL IN

TO ANOTHER

CONTAINER. ABSORB REMAINING MATERIAL WITH PROPER ABSORBENT SUCH AS SAND, EARTH, VERMICULITE. SWEEP UP AND DISPOSE AS SOLID WASTE.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:MFR RECOMMENDS NONE.

Ventilation:MFR RECOMMENDS NONE

Protective Gloves:RUBBER

Eye Protection:FULL FACE SHIELD/SFTY GOG

Other Protect

ive Equipment:GLOVES: ALSO PLASTIC OIL RESISTANT

Supplemental Safety and Health

SPEC: MIL-L-2105C. SAE 80W/90. CONTAINER 1 QT CAN KEY1:N1.

=====  
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:149C, 300F

Spec Gravity:0.936

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER LIQUID WITH MINERAL OIL ODOR.

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS: CHROMIC

ACID, H\*2O\*2, BROMINE

Hazardous Decomposition Products:CO & CO\*2

=====  
===== Disposal Considerations =====

Waste Disposal Methods:WASTE DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be

accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.