

MOBIL OIL CORP. -- MOBILUBE HD 85W-140,MIL-L-2105C -- 9150-01-035-5396

=====
Product Identification
=====

Product ID:MOBILUBE HD 85W-140,MIL-L-2105C

MSDS Date:01/01/1985

FSC:9150

NIIN:01-035-5396

MSDS Number: BGGPW

=== Responsible Party ===

Company Name:MOBIL OIL CORP.

Emergency Phone Num:(212)883-4242

CAGE:3U278

=== Contractor Identification ===

Company Name:MOBIL CORP

Address:150 E 42ND ST

Box:

City:NEW YORK

State:NY

ZIP:10017-5612

Country:US

Phone:212-883-4242

CAGE:57635

Company Name:MOBIL OIL CORP.

Address:3225 GALLOWS RD

City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:1-800-662-4525

CAGE:3U278

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: >90%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES &/OR OTHER INGRED

Fraction by Wt: PINT

INGEST,IMMED

GIVE 1 TO 2 G LASSES WATER,CALL MD FOR WAY TO INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point:400F COC

Extinguishing Media:CO*2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:FIREFIGHTERS MUST USE SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST, DEATOMACEOUS EARTH OR OTHER ABSORBENT. SHOVEL UP & DISPOSE OF IN APPROVED HAZARDOUS WASTE DISPOSAL FACILITY. U.S. COAST GUARD REG REQUIRE IMMED REPORTING OF S PILLS THAT COULD REACH WATERWAYS/INTERMIT DRY CRKS

===== Handling and Storage =====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS REQUIRED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MFR STATES NO SPECIAL REQUIREMENTS UNDER NORMAL USE A W/ADEQ VENTI

L

Ventilation:ADEQUATE

Protective Gloves:OIL IMPERVIOUS

Eye Protection:NORMAL I.H. PRACTICES

Supplemental Safety and Health

MFR STATES HARMFUL CONC OF MISTS &/OR VAP ARE UNLIKELY TO VE ENCONTERED THROUGH ANY CUSTOMARY OR REASONABLY FOR SEEABLE HANDLING,USE OR MISUSE OF THIS PRODUCT. VAP PRESSURE:MM HG 20C 600F

Solubility in Water:NEGLIGLE

Appearance and Odor:ASTM 7.0 LIQUID,MILD ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Av

oid:YES

STRONG OXIDIZERS

Stability Condition to Avoid:STRONG OXIDATION

Hazardous Decomposition Products:CARBON MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM DISSOLVE WASTE IN A SOLVENT & DISPOSE BY SUPERVISED INCINERATION IN COMPLIANCE W/APPROPRIATE REGULATIONS. DISPOSAL MUST BE IAW FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by

elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.