View NSN Online: https://aerobasegroup.com/nsn/6850-01-037-9015

SHELL OIL COMPANY -- ACETONE -- 6850-01-037-9015

Product ID:ACETONE MSDS Date:01/01/1987 FSC:6850 NIIN:01-037-9015 Kit Part:Y MSDS Number: BGGVV === Responsible Party === Company Name: SHELL OIL COMPANY Address: HEALTH, SAFETY AND ENVIRONMENT Box:4320 City:HOUSTON State:TX ZIP:77210 Country:US Info Phone Num:713-241-4819 Emergency Phone Num:713-473-9461 CAGE:54527 === Contractor Identification === Company Name: SHELL OIL COMPANY

Company Name:SHELL OIL COMPANY Box:2463 City:HOUSTON State:TX ZIP:77210 Country:US Phone:800-231-6950 CAGE:54527

Ingred Name:ACETONE (SARA III) CAS:67-64-1 RTECS #:AL3150000 Fraction by Wt: 100%. OSHA PEL:1000PPM ACGIH TLV:750PPM/1000STEL;9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Effects of Overexposure:EYE/SKIN

## ;IRR;INH:NOSE,THROAT,HEADACHE,DIZZINESS,NAUSEA ,UNCONSCIOUSNESS.VAORS DEADEN SENSE SMELL

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE: IMMED FLUSH W/PLENTY OF WATER. SKIN: WASH W/SOAP&WATER. RMV CONTAM CLTHG&SHOES. INGEST: INDUCE VOMIT. RPT UNTIL VOMIT IS C LEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN. ====== Flash Point:-15F,26C,TCC Lower Limits:2.6 Upper Limits:12.8 Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*20 FOG. Fire Fighting Procedures: USE SCBA & PROTECT-EQUIPM. IN CONFINED FIRE SPACES. Unusual Fire/Explosion Hazard: TREAT AS AN EXTREMELY FLAMMABLE LIQUID. Spill Release Procedures: ELIM.ALL SURCES OF IGN.IMM.& EVAC.AREA.BE PREPARED FOR FIRE.WEAR APPROPIATE PROTECT.CLOTHNG & **RESP.PROTECT.EQUIP.SHUT OFF LEAK** .VENTIL.AREA.DKE&PUMP LG.SPILLS INTO SALVAGE CONT.ABSORB SMALL SPILLS.SCOOP UP ALL CNTAM.SOIL&STORE IN SALVAGE CONT. Handling and Storage Precautions: STORE IN COOL, DRY WELL VENTED LOW FIRE RISK AREA. PROTECT FROM HEAT, SHOCK, FRICTION. KEEP CONTAINERS CLOSED. Other Precautions: ACETONE IS A VERY VOLATLE, EXTREMELLY FLAMM LIQ. KEEP AWAY FROM ANY SOURCES OF IGN. GROUND ALL CONT. WHEN POURING OR TRANSFERRING.DO NOT EAT, SMMOKE NEAR PRODUCT. WASH W/SOAP & WTR BEFORE EAT, SMOKE. Respiratory Protection: USE NIOSH APPVD RESP. PROTECT. EQUIPM S REQD TO PREVENT OVEREXPOSRE. Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves: IMPERVIOUS Eye Protection:GOGGLES Other Protective Equipment: AS REQUIRED TO PREVENT PROLONGED CONTACT. Supplemental Safety and Health THIS IS A CURE STABILIZER IN A 1 OZ BOTTLE AND IS PRT C OF A KIT WHIC

Н

CONTAINS 1 GL CAN OF MAGNETIC RUBBER MTERIAL AN 2 OZ BOTTLE OF CATALYST KEY1:F2

HCC:F2 Boiling Pt:B.P. Text:133F,56C Vapor Pres:181 Vapor Density:2.0 Spec Gravity:0.8 Evaporation Rate & amp; Reference:5.6 Solubility in Water:COMPLETE Appearance and Odor:COLORLESS MOBILE LIQUID.MILD ODOR. Percent Volatiles by Volume:100.

Stability Indicator/Materia Is to Avoid:YES REACTS WITH STRONG OXIDIZING AGENTS. Stability Condition to Avoid:KEEP AWAY FROM HEAT,SPARKS,FLAME.NO SMOKING Hazardous Decomposition Products:INCOMPLETELY BURNED CARBON PRODUCTS, CO\*2, CO.

Waste Disposal Methods:DO NOT ALLOW PROD TO ENTER SEERS,WATERWAYS.NOTIFY AUTHORITIES IF THIS HAPPENS OR IS THREATENED.

Disclaimer (provided with this information by the compiling agencies): This informatio

n is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.