

P.D.I., INCORPORATED -- PLASTIC DIP INSULATING COMPOUND, ELECT. -- 5970-01-038-0592

=====  
Product Identification  
=====

Product ID:PLASTIC DIP INSULATING COMPOUND, ELECT.

MSDS Date:06/01/1989

FSC:5970

NIIN:01-038-0592

MSDS Number: BGGWG

=== Responsible Party ===

Company Name:P.D.I., INCORPORATED

Address:3760 FLOWERFIELD ROAD

City:BLAINE

State:MN

ZIP:55434

Country:US

Info Phone Num:612-785-2156

Eme

Agency Phone Num:612-785-2156

Preparer's Name:STEVE CARTER

CAGE:MO678

=== Contractor Identification ===

Company Name:P D I INC

Address:3760 FLOWEFIELD RD

Box:City:CIRCLE PINES

State:MN

ZIP:55014

Country:US

Phone:612-785-2156

CAGE:55638

Company Name:P.D.I., INCORPORATED

Address:3760 FLOWERFIELD ROAD

Box:City:BLAINE

State:MN

ZIP:55434

Country:US

Phone:612-785-2156

CAGE:MO678

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE)

(SARA III)  
CAS:71-55-6  
RTECS #:KJ2975000  
Fraction by Wt: 22-24%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:350 PPM/450 STEL  
ACGIH TLV:350 PPM/450STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:HYDROTREATED HEAVY NAPHTHA  
CAS:64742-48-9  
Fraction by Wt: 24-26%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:500 PPM  
ACGIH TLV:300 PPM

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 12-14%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:200 PP  
M/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:N-HEPTANE  
CAS:142-82-5  
RTECS #:MI7700000  
Fraction by Wt: 11-13%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:500 PPM/500 STEL  
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:RESIN  
Fraction by Wt: 27%  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health

Hazards Acute and Chronic:ACUTE-CNS, CVS, PNS, LIVER, KIDNEY, LUNGS, RESPIRATORY SYSTEM AND SKIN. CHRONIC-BRAIN AND NERVOUS SYSTEM DAMAGE (REFERRED TO AS SOLVENTS OR PAINTERS SYNDROME). DRYING OR CRACKING OF SKIN.

Explanation of Carcinogenicity:NONE OF THE INGREDIENTS IN THIS CHEMICAL ARE LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:HEADACHE, DIZZINESS, DROWSINESS, FATIGUE, IRREGULAR HEARTBEAT, SKIN AND EYE IRRITATION.

Medical Cond Aggravated by Expos  
ure:PRE-EXISTING HEART, LIVER, KIDNEY  
AND LUNG DISORDERS.

=====  
===== First Aid Measures =====

First Aid:INGESTION-CONTACT PHYSICIAN OR POISON CONTROL IMMEDIATELY. INHALATION-REMOVE TO FRESH AIR. GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED. EYE-FLUSH WITH LARGE AMOUNTS OF WATER. IF IRRITATION CONTINU ES, CONTACT PHYSICIAN. SKIN-WASH WITH SOAP AND WATER.

=====  
===== Fire Fighting Measures =====

Flash Point Met

hod:TCC

Flash Point:24.0F,-4.4C

Lower Limits:1.1

Upper Limits:10.5

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FULL FACED SELF CONTAINED BREATHING APPARATUS, OPERATED IN PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE.

Unusual Fire/Explosion Hazard:THIS MATERIAL IS FLAMMABLE AND MAY BE IGNITED BY HEAT, SPARKS, FLAME OR STATIC ELECTRICITY.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP WITH FLOOR ABSORBENT. TRANSFER TO HOOD. PREVENT RUN-OFF TO SEWERS. ELIMINATE IGNITION SOURCES. VENTILATE TO MAINTAIN EXPOSURE BELOW PEL'S.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM SPARKS, FLAME AND HIGH HEAT SOURCES. DO NOT STORE ABOVE 120F.

Other Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:ORGANIC VAPOR CARTRIDGE

, NIOSH/MSHA APPROVED.

Ventilation:USE MECHANICAL VENTILATION TO MAINTAIN EXPOSURE BELOW P.E.L. AND LOCAL EXHAUST IF NEEDED AS SUPPLEMENTAL VENTILATION.

Protective Gloves:IMPERVIOUS GLOVES

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:IMPERVIOUS CLOTHING/BOOTS AS NEEDED.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING PRODUCT.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:B.P. Text:160F,71C

Vapor Density:4.6

Spec Gravity:0.92-0.94

Evaporation Rate & Reference:4.5

Solubility in Water:INSOLUBLE

Appearance and Odor:VARIOUS COLORS-HONEY LIKE SUBSTANCE-CHARACTERISTIC ODOR.

Percent Volatiles by Volume:3.90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, BASES,OXIDIZING AGENTS, SELECTED AMINES. CHEMICALLY ACTIVE METALS, POWDERS.

Stability Condition to Avoid:NONE

Hazard

ous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, POSSIBLY PHOSGENE AND HYDROGEN CHLORIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly

or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.