

ALLOY RODS CORPORATION -- ATOM ARC 8018 0.187 -- 3439-01-038-3773

=====  
Product Identification  
=====

Product ID:ATOM ARC 8018 0.187

MSDS Date:06/06/1986

FSC:3439

NIIN:01-038-3773

MSDS Number: BGGXQ

=== Responsible Party ===

Company Name:ALLOY RODS CORPORATION

Address:WILSON AVENUE

Box:517

City:HANOVER

State:PA

ZIP:17331

Info Phone Num:717-637-8911

Emergency Phone Num:717-637-8911

CAGE:84021

=== C

Contractor Identification ===

Company Name:ESAB GROUP INC

Address:801 WILSON AVENUE

Box:517

City:HANOVER

State:PA

ZIP:17331

Country:US

Phone:717-637-8911 OR 800-933-7070

CAGE:84021

=====  
Composition/Information on Ingredients  
=====

Ingred Name:IRON

CAS:7439-89-6

RTECS #:NO4565500

Other REC Limits:5MG/M\*3

OSHA PEL:10MG/M\*3

ACGIH TLV:5MG/M\*3

Ingred Name:SILICON

CAS:7440-21-3

RTECS #:VW0400000

Other REC Limits:10MG/M\*3

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingr

ed Name:SODIUM SILICATE  
CAS:6834-92-0  
RTECS #:VV9275000  
OSHA PEL:5MG/M\*3 (RESP. DUST)  
ACGIH TLV:0.1MG/M\*3(RESP.DUST)

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)  
CAS:1317-65-3  
RTECS #:EV9580000  
Other REC Limits:10MG/M\*3  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Other REC Limits:10MG/M\*3  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:MANGANESE (SARA III)  
CAS:7439-96-5  
RTECS #:OO9275000  
Other R  
EC Limits:5MG/M\*3 (C)  
OSHA PEL:(C) 5 MG/M3 DUST  
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:NICKEL (SARA III)  
CAS:7440-02-0  
RTECS #:QR5950000  
OSHA PEL:1 MG/M3  
ACGIH TLV:1 MG/M3; 9192

Ingred Name:POTASSIUM SILICATE  
CAS:1312-76-1  
OSHA PEL:5MG/M\*3 (RESP.DUST)  
ACGIH TLV:0.1MG/M\*3(RESP.DUST)

Ingred Name:CALCIUM FLUORIDE  
CAS:7789-75-5  
RTECS #:EW1760000  
Other REC Limits:2.5MG/M\*3  
OSHA PEL:2.5 MG/M3 (F)  
ACGIH TLV:2.5 MG/M3 (F); 8990

Ingred Name:POTASSIUM FELDSPAR  
Other REC Limits:10MG/M\*3(NUISANCE)  
OSH

A PEL:NOT LISTED  
ACGIH TLV:NOT LISTED

Ingred Name:ZIRCON (ZIRCONIUM IV,SILICATE)  
CAS:14940-68-2  
RTECS #:ZH9000000  
Other REC Limits:5 MG/M\*3  
OSHA PEL:5 MG/M3/10 STEL (ZR)  
ACGIH TLV:5 MG/M3/10 STEL (ZR)

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Health Hazards Acute and Chronic:ACUTE:METALLIC TASTE,NAUSEA,TIGHTNESS  
OF CHEST,FEVER,DIZZINESS,DRYNESS,IRRITATION OF EYES,NOSE,THROAT.  
CHRONIC:EXCESSIVE LEVELS MAY  
CAUSE BRONCHIAL ASTHMA,LUNG  
FIBROSIS,SIDEROSIS. ARC RAYS CAN INJURY EYES & BURN SKIN. ELECTRIC  
SHOCK CAN KILL.  
Explanation of Carcinogenicity:NICKEL IS A SUSPECTED HUMAN CARCINOGEN.  
Effects of Overexposure:SEE HEALTH HAZARDS.  
Medical Cond Aggravated by Exposure:AGGRAVATION OF EXISTING RESPIRATORY  
OR ALLERGIC CONDITIONS. HIGHER LEVEL OF LUNG RELATED PROBLEMS AMONG  
SMOKERS.

=====  
===== First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE & OBT  
AIN PROMPT MEDICAL ATTENTION. IF  
NOT BREATHING,GIVE CPR. IF UNCONSCIOUS,GIVE OXYGEN. EMPLOY FIRE AID  
TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:APPROPRIATE FOR SURROUNDING FIRE.  
Unusual Fire/Explosion Hazard:WELDING ARCS & SPARKS CAN IGNITE  
COMBUSTIBLE PRODUCTS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP ANY GRINDI

NG DUST OR WASTE RESIDUE &  
PLACE IN APPROPRIATE DISPOSAL CONTAINER.

=====  
Handling and Storage  
=====

Other Precautions: TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES.  
MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES. AVOID ELECTRICAL SHOCK  
BY MAINTAINING DRY WORK AREA.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection: FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR IN  
CONFINED SPACES OR WHERE VENTILATION DOES NOT  
KEEP EXPOSURE BELOW  
TLV.

Ventilation: LOCAL EXHAUST

Protective Gloves: WELDER'S GLOVES

Eye Protection: HELMET OR FACE SHIELD WITH FILTER LENS

Other Protective Equipment: SUBSTANTIAL DARK CLOTH, ARM  
PROTECTOR, APRON, HAT, SHOULDER PROTECTION.

Work Hygienic Practices: WASH AFTER HANDLING.

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC: N1

Appearance and Odor: WELDING ROD 0.187 INCHES DIAMETER BY 14 INCHES  
LONG.

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid: YES

Hazardous Decomposition Products: FUMES OF METALS & METAL  
OXIDES, CO, CO\*2, NO\*2, O\*3, FLUORIDES

=====  
Disposal Considerations  
=====

Waste Disposal Methods: DISPOSE OF IAW FEDERAL, STATE & LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States

ates of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.