

BRULIN & COMPANY,INC. -- FORMULA 715N -- 6850-01-045-7929

=====
Product Identification
=====

Product ID:FORMULA 715N

MSDS Date:09/17/1986

FSC:6850

NIIN:01-045-7929

MSDS Number: BGHMG

=== Responsible Party ===

Company Name:BRULIN & COMPANY,INC.

Box:270-B

City:INDIANAPOLIS

State:IN

ZIP:46206-0270

Country:US

Info Phone Num:317-923-3211

Emergency Phone Num:1-800-428-7149

Preparer's Name:MSDS HAS INIT

IALS "JR"

CAGE:DO828

=== Contractor Identification ===

Company Name:BRULIN & COMPANY,INC.

Box:270-B

City:INDIANAPOLIS

State:IN

ZIP:46206-0270

Country:US

Phone:317-923-3211

CAGE:DO828

Company Name:BRULIN AND CO INC

Address:2920 DR ANDREW J BROWN AVE

Box:270

City:INDIANAPOLIS

State:IN

ZIP:46205-0270

Country:US

Phone:317-923-3211

CAGE:94058

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT NAPHTHA,HEAVY AROMATIC

CAS:64742-94-5

Fraction by Wt: 30-50%.

Other R

EC Limits:100 PPM

Ingred Name:2-BUTOXYETHANOL

CAS:111-76-2

RTECS #:KJ8575000

Fraction by Wt: 10-30%.

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

Ingred Name:ETHANOLAMINE

CAS:141-43-5

RTECS #:KJ5775000

Fraction by Wt: 1.-5%.

OSHA PEL:3 PPM/6 STEL

ACGIH TLV:3 PPM/6 STEL; 9192

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: D

IZZINESS; SKIN & EYE

IRRITATION; CHRONIC: NONE KNOWN

Effects of Overexposure:INHAL: DIZZINESS; SKIN/EYES: IRRITATES, SKIN
DRYNESS

Medical Cond Aggravated by Exposure:PRE-EXISTING RESPIRATORY
CONDITIONS.

=====
===== First Aid Measures =====

First Aid:INHAL: REMOVE TO FRESH AIR. ADMINISTER OXYGEN IF BREATHING IS
DIFFICULT. GET MEDICAL ATTN.; EYES: FLUSH W/LARGE AMTS. OF WATER
FOR 15 MIN LIFTING UPPER & LOWER LIDS OCCASIONALLY. GET MEDICAL
A

TTN.; SK IN: WASH W/MILD SOAP & WATER. REMOVE CONTAMINATED
CLOTHING & LAUNDER BEFORE REUSE. INGEST: DO NOT INDUCE VOMITING.
KEEP PERSON WARM, QUIET & GET IMMEDIATE MEDICAL ATTN.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:152F/67C

Lower Limits:6.5

Upper Limits:0.9

Extinguishing Media:WATER OR CARBON DIOXIDE

Fire Fighting Procedures:SELF-CONTAINED RESPIRATORY EQUIPMENT SHOULD BE
PROVIDED FIRE-FIGHTING PERSONNEL. WATER FOG M

AY BE USED TO COOL
CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard:NEVER USE CUTTING OR WELDING TORCH ON OR
NEAR DRUM (EVEN EMPTY)

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA WELL. USE APPROPRIATE
PROTECTIVE EQUIPMENT. ABSORB ONTO A SOLID ABSORBENT (EG.
VERMICULITE) & SHOVEL INTO APPROVED CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BETWEE
N 40F & 120F IN A DRY
PLACE.

Other Precautions:AVOID BREATHING SPRAY MIST.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC
VAPOR/MIST WHEN TLV EXCEEDED.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN