

BATTENFELD-AMERICAN,INC. -- MIL-L-2105,LUBRICATING OIL,GEAR,GRAD 85W140 --  
9150-01-048-4591

=====  
===== Product Identification =====

Product ID:MIL-L-2105,LUBRICATING OIL,GEAR,GRAD 85W140

MSDS Date:01/01/1985

FSC:9150

NIIN:01-048-4591

MSDS Number: BGHTB

=== Responsible Party ===

Company Name:BATTENFELD-AMERICAN,INC.

Emergency Phone Num:716-822-8410

CAGE:JO766

=== Contractor Identification ===

Company N

ame:BATTENFELD AMERICA INC

Address:1575 CLINTON ST

Box:City:BUFFALO

State:NY

ZIP:14206

Country:US

Phone:716-822-8410

CAGE:61808

Company Name:BATTENFELD-AMERICAN,INC.

CAGE:JO766

=====  
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: UNK

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES

Fraction by Wt: UNK

=====  
===== Hazards Identification ==

=====

Effects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.

===== First Aid Measures =====

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.  
INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

===== Fire Fighting Measures =====

Flash Point:325F/163C OC  
Lower Limits:UNK  
Upper Limits:UNK  
Extinguishing Media:CO\*2, FOAM, DRY CHEM.  
Fire Fighting Procedure  
s:WEAR SELF-CNTND BRTHG APP  
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H\*2O SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS:LG SPILL:DI KE W COMMERCIAL ABSORBENT,PUMP INTO COVERED DRUMS.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED. MAINTAIN STANDARD HYGIENE FOR CHEM HANDLING  
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED RESPIRATOR FOR OIL MIST.  
Ventilation:NO SPECIAL REQUIREMENTS W ADEQUATE VENT.  
Protective Gloves:BUNA-N  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:NONE

Supplemental Safety and Health  
UNDER MIL SPEC L-21905,ITEM MEETS REQUIREMENTS FOR GRADE 85W140.

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>700F/371C  
Spec Gravity:0.89  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:FLUID OIL-TERPENE  
Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS.  
Stability Condition to Avoid:NONE  
Haza  
rdous Decomposition Products:INCOMPLETELY BURNED CARBON PRODUCTS,  
CO\*2, CO.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF  
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in n  
o manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.