

FISKE BROTHERS REFINING CO. -- FISKE'S 722 OIL -- 9150-01-048-9554

===== Product Identification =====

Product ID:FISKE'S 722 OIL

MSDS Date:11/01/1985

FSC:9150

NIIN:01-048-9554

MSDS Number: BGHYB

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO.

Address:129 LOCKWOOD STREET

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

P

reparer's Name:ROBERT J.SIBILIA

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-355-8041

CAGE:6A

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Other REC Limits:5MG/CUM AS OILMIST

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:UNIDENTIFIED COMPONENTS

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN OR
RESPIRATORY TRA

CT. CHRONIC:NO DATA AVAILABLE,POSSIBLE DERMATITIS.

Effects of Overexposure:MAY CAUSE IRRITATION OF SKIN,EYES, RESPIRATORY
TRACT;LOW ORDER OF TOXICITY.Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE
WORSEN.=====
First Aid Measures
=====First Aid:EYES:WASH WITH PLENTY OF WATER;CALL A PHYSICIAN. SKIN:WASH
WITH SOAP & WATER. INHALATION:REMOVE TO FRESH AIR,CALL A PHYSICIAN.=====
Fire Fighting Measures
=====

Flash Point Method:COC

Flash Point:275F/135C

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM,DRY CHEMICAL,CO2,WATER SPRAY

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED
AREA.

Unusual Fire/Explosion Hazard:DO NOT STORE WITH STRONG OXIDANTS.

=====
Accidental Release Measures
=====Spill Release Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE
INERT ABSORBENT MATERIAL & RECOVER FOR PROPER DISPOSAL.

Neutral

izing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY AND WELL VENTILATED AREA. KEEP AWAY FROM HEAT, OPEN FLAMES.

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPOR/MIST IF ABOVE TLV/PEL.

Ventilation:LOCAL/GENERAL TO MAINTAIN BELOW TLV/P

EL

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:FULL SKIN & EYE PROTECTION

Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES;DO NOT BREATHE VAPORS/MIST.

Supplemental Safety and Health

MSDS RECEIVED BY DGSC-SLM:MARCH 4, 1988, ORIGINALLY AND AGAIN NOVEMBER, 1993.

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F/288C

Vapor Pres:5.0

Spec Gravity:0.81

Evaporation Rate & Reference: