

FISKE BROTHERS REFINING CO -- FISKE GG OIL -- 9150-01-048-9554

===== Product Identification =====

Product ID:FISKE GG OIL

MSDS Date:04/01/1994

FSC:9150

NIIN:01-048-9554

MSDS Number: BGHYC

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE, STATION A.

Box:8038

City:TOLEDO

State:OH

ZIP:43605-3843

Country:US

Info Phone Num:419-691-2491

Emergency Phone Num:800-

255-3924 CHEMTEL

Preparer's Name:JAMES R. KONTAK

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804

-355-8041
CAGE:6A908

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL
CAS:8012-95-1
RTECS #:PY8030000
Other REC Limits:5MG/CUM,AS OIL MIST
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3 (MIST); 9596

Ingred Name:UNIDENTIFIED COMPONENTS
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogeni
city:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CONTACT MAY CAUSE EYE IRRITATION.
PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE IRRITATION. INHALATION
OF VAPORS OR MISTS NEEDS TO BE MINIMIZED. ASPIRATION DURING
INGESTION OR VOMITING MAY CAUSE PULMON ARY INJURY.
Explanation of Carcinogenicity:NO INGREDIENT OF A CONCENTRATION OF 0.1%
OR GREATER IS LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN.
Effects of Overexposure:EYES-IRRITATION. SKIN-IRRITATION. INGESTION
(
ASPIRATION)-PULMONARY INJURY. INHALED-NONE STATED.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:IN ALL CASES GET PROMPT MEDICAL ATTENTION. EYES-FLUSH WITH
WATER FOR 15 MINUTES. SKIN-REMOVE CONTAMINATED CLOTHES. WASH WITH
MILD SOAP & WATER. INHALED-REMOVE TO FRESH AIR. INGESTED-DO NOT
INDUCE VOMI TING!

=====
Fire Fighting Measures
=====

Flash Poin

t Method:COC

Flash Point:275F,135C

Lower Limits:0.9

Upper Limits:7.0

Extinguishing Media:WATER SPRAY (FOG), CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL FIRE FIGHTER'S PROTECTIVE GEAR. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND OR WELD, AS THEY MAY EXPLODE.

=====
Accidental Release Measures =====

Spill Release Procedures:RECOVER LIQUID. WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS OR WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDIZING AGENTS.

Other Precautions:AVOID BREATHING OIL MIST. REMOVE OIL-SOAKED CLOTHES AND LAUNDRY BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

=====
Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV(S).

Protective Gloves:OIL RESISTANT-NITRILE.

Eye Protection:GOGGLES.

Other Protective

Equipment:OIL RESISTANT APRON.

Work Hygienic Practices:WASH HANDS AFTER HANDLING AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDRY CONTAMINATED CLOTHES BEFORE REUSE.

Supplemental Safety and Health

MSDS PRESENTED BY CAGE 6A908 FOR CONTRACT NUMBER SP0451-96-M-Q455.

=====
Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F/288C

Melt/Freeze Pt:M.P/F.P Text:LIQUID

Vapor Pres:5

Spec Gravity:0.81

Evaporation Rate & Reference: