EASTMAN KODAK COMPANY -- 192 7698,FLEXCOLOR DEVLPR,PART-C (PRE 4/86) 6750-01-050-7789

Product ID:192 7698, FLEXCOLOR DEVLPR, PART-C (PRE 4/86) MSDS Date:03/01/1979 FSC:6750 NIIN:01-050-7789 Kit Part:Y MSDS Number: BGJBB === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-722-5151 Emergency Phone Num:716-722-5151 CAGE:19139 === C ontractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 Ingred Name:4-(N-ETHYL-N-2-HYDROXYETHYL)-2-METHYLPHENYLENEDIAMINE SULFATE; WT % RANGE:15-20% (DISSOCIATES TO 10-15% H*2SO*4 IN WATER) CAS:25646-77-9 RTECS #:KJ6477000 Fraction by Wt: 17.0% Other REC Limits:1MG/CUM (H*2 SO*4) OSHA PEL:17.5 Ingred Name:WATER; WT % RANGE:80-85 CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 82.5% Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NOT KNOWN Effects of Overexposure: INHALED: GAS(SO*2) IRRITATS; EYE/SKIN: CONTACT W LIQ/GAS IRRITATS.REPEATED CONTACT MAY CAUSE ALLERGY.

First Aid:INHAL:REMOVE FROM EXPOSURE;EYES:FLUSH IMMEDIATELY WITH PLENTY OF WATER-GET MEDICAL ATTENTION SKIN: FLUSH IMMEDIATELY WITH PLENTY OF WATER Flash Point:NONE Extinguishing Media: EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER. ======= Spill Release Procedures: STOP LEAK WITHOUT RISK. EVACUATE UNPROTECTED PERSONS.NEUTRALIZE WITH SODIUM BICARBONATE.DILUTE WITH COPIOUS AMOUNTS OF WATER AND FLUSH TO SEWER IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL EFFLUENT LAWS. Handling and Storage Precautions: STORE IN COOL, DRY, LOW FIRE RISK AREA.KEEP TIGHTLY SEALED PROTECT FROM PHYSICAL DAMAGE.STORE AWAY FROM MINERAL ACIDS AND STRONG ALKALI. Other Precautions: ROUTINE USE OF A NON-ALKALINE (ACID) TYPE HAND CLEANER WILL HELP MINIMIZE THE POSSIBILITY OF ALLERGIC SKIN REACTION Respiratory Protection: NONE SHOULD BE NEEDED Ventilation:MECHANICAL(GENERAL) RECOMMENDED.LOCAL EXHAUST IF NEEDED

SOLUTION NO:3650, AND ACCESSION #UNKNOWN OF THIS PART; SEE PNI E FOR NEW FORMULA TION OF THIS PART; ALSO SEE PNI A, B,& DFOR OTHER

PARTS; NOTE:CORR LIQ NOS IS BETTER THAN SULFURIC ACID,UN1830; KEY1:C1

FORMULATION.EFFECTIVE DATE OF FORMULATION CHANGE IS NOT KNOWN;

Other Protective Equipment: AS NECESSARY TO PREVENT SKIN CONTACT

HCC:C2 Boiling Pt:B.P. Text:212F/100C Vapor Pres:17 Vapor Density:0.6 Spec Gravity:1.08 Solubility in Water:COMPLETE App

Protective Gloves: IMPERVIOUS Eve Protection: SAFETY GLASSES

Supplemental Safety and Health ITEM IS A 3 PART KIT; THIS ENTRY

DESCRIBES PART C OF OLD

earance and Odor:REDDISH-BROWN,SULFUR DIOXIDE ODOR Percent Volatiles by Volume:62%

Stability Indicator/Materials to Avoid:YES MINERAL ACIDS AND STRONG ALKALI Hazardous Decomposition Products:SUFLUR DIOXIDE

Waste Disposal Methods:NEUTRALIZE WITH SODIUM BICARBONATE.DILUTE THEN FLUSH TO SEWER WITH COPIOUS AMOUNTS OF WATER.FEDERAL,STATE AND LOCAL EFFLUEN T LAWS TAKE PRECEDENCE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.