

INLAND PACKAGING -- INNERBOND I2510 FLUID, VISCOSITY 100 -- 9150-01-056-7346

=====
Product Identification
=====

Product ID:INNERBOND I2510 FLUID, VISCOSITY 100

MSDS Date:01/01/1987

FSC:9150

NIIN:01-056-7346

MSDS Number: BGJMJ

=== Responsible Party ===

Company Name:INLAND PACKAGING

Address:209 PETERSON DRIVE

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Info Phone Num:502-737-6758

Emergency Phone Num:502-737-6758

CAGE:66172

=== Contractor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYLPHENYL POLYSILOXANE (SILICONE OIL)

CAS:63148-52-7

Fraction by Wt: 100.0%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Report

s of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:LOW TOXICITY;MAY CAUSE EYE
IRRITATION.(PER MSDS)NO OTHER ILL EFFECTS ARE KNOWN.
Effects of Overexposure:LOW TOXICITY PER MSDS.MAY CAUSE EYE IRRITATION
OR DISCOMFORT.NO OTHER DATA AVAILABLE.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH THOROUGHLY WITH LARGE VOLUMES OF WATER FOR 15
MINUT
ES, BEING CAREFUL TO RINSE UNDER LIDS. GET MEDICAL ATTENTION
IF IRRITATION PERSISTS AFTER 24 HOURS. SKIN: WASH WITH SOAP AND
LARGE VOLUME S OF WATER. INHALATION: NOT LIKELY. IF IT SHOULD
OCCUR, CALL DOCTOR. INGESTION: IF CONSCIOUS, INDUCE VOMITING. GET
MEDICAL ATTENTION AS NEEDED.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:527F,275C
Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.
Fire Fighting Procedures
:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SWEEP UP WITH VERMICULITE INTO A STEEL DRUM

=====
===== Handling and Storage =====

Handling
and Storage Precautions:STORE IN COOL, DRY AND VENTILATED
AREA.KEEP AT ROOM TEMPERATURE.KEEP AWAY FROM HEAT AND
MOISTURE.PROTECT AGAINST STATIC STATIC ELECTRICITY.
Other Precautions:WASH THOROUGHLY AFTER HANDLING .DO NOT EAT,DRINK OR
SMOKE INWORK AREA.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NEEDED IF THERE IS AN ADEQUATE
VENTILATION.
Ventilation:GENERAL TO MAINTAIN AN ADEQUATE VENTILATION.
Protective Gloves:AS NEE

DED.
Eye Protection:SAFETY GOGGLES.
Other Protective Equipment:APRON,EYE-WASH FACILITIES.
Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;WASH THOROUGHLY AFTER USE.
Supplemental Safety and Health NONE.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>300F/149C
Spec Gravity:0.99
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR COLORLESS LIQUID, ODOR NOT DESCRIBED

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid:YES
MINERAL ACIDS AND STRONG BASES
Stability Condition to Avoid:HIGH TEMPERATURES, IGNITION SOURCES
Hazardous Decomposition Products:SIO*2,CO*2,CARBON PRODUCTS

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.