View NSN Online: https://aerobasegroup.com/nsn/5970-01-062-0884

Product ID:F CATALYST MSDS Date:01/01/1987 FSC:5970 NIIN:01-062-0884 MSDS Number: BGJVQ === Responsible Party === Company Name: ELECTRICAL INSULATION (DIST), DOW CORNING CORP (MFR). Emergency Phone Num:517-496-5900 CAGE:7L738 === Contractor Identification === Company Name: DOW CORNIN G CORP Address:2200 W SALZBURG RD Box:City:AUBURN State:MI ZIP:48611 Country:US Phone:517-496-4388 CAGE:71984 Company Name: ELECTRICAL INSULATION SUPPLIES INC Address:2100 MAGNOLIA ST Box:267 City:RICHMOND State:VA ZIP:23223-2310 Country:US Phone:804-649-9221 CAGE:7L738

Ingred Name:SILICONE COMPOUND Fraction by Wt: 95.0%

Ingred Name:STANNOUS OCTOATE Fraction by Wt: 5.0% OSHA PEL:S, 0.1 MG/M3 (SN) ACGIH TLV:S, 0.1 MG/M3 (SN) Effects of Overexposure:EYE:IRRT,CORN INJURY POS.SKN:FLUSH,IRRT,BURN,INHL:IRRT,PAIN.INGEST:POSS ALLERGIC REACT.

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP&WATER. RMV CONTAM CLTHG&SHOES. INGEST:INDUCE VOMIT. RPT UNTIL VOMIT IS C LEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

Flash Point:7250F/121C OC Extinguishing Media:WATER FOG, CO\*2, DRY CHEM, FOAM Fire Fighting Procedures:USE SCBA & FULL BODY PROTECT. Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL.

=======

Handling and Storage Precautions:STORE BELOW 90F. USE REASONABLE CARE. Other Precautions:NONE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE Ventilation:MECHANICAL IS RECOMMENDED Protective Gloves:NONE Eye Protection:SAFETY GLASSES Supplemental Safety and Health MSDS DTD 70CT85. PT B OF TWO-PART A&B KIT. DO NOT SEPARATE IN STORAGE OR SHIPMENT.KEY1;N1.

HCC:N1 Bo iling Pt:B.P. Text:>300F Vapor Pres: