

EASTMAN KODAK COMPANY -- 180 3972,MICROFILM BLEACH & REPLENISHER -- 6750-01-064-7321  
===== Product Identification =====

Product ID:180 3972,MICROFILM BLEACH & REPLENISHER

MSDS Date:01/01/1985

FSC:6750

NIIN:01-064-7321

MSDS Number: BGJYR

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Eme

rgency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:SULFAMIC ACID(15-20%) (CAS #5329-14-6)

CAS:5329-14-6

RTECS #:WO5950000

Fraction by Wt: 17.5%

Ingred Name:POTASSIUM BICHROMATE (SARA III)

CAS:7778-50-9

RTECS #:HX

7680000

Fraction by Wt: 7.5%

OSHA PEL:C,0.1 MG/M3 CRO3

ACGIH TLV:0.5 MG CR/M3; 9293

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED(70-80%)

Fraction by Wt: 75.0%

=====  
Hazards Identification  
=====

Effects of Overexposure:EYES:LIQD CONTACT CAN CAUSE  
BURNS;SKIN:PROLNKD/REPEATD CONTACT MAY CAUSE BURNS/ALLERGIC  
REACTION.

=====  
First Aid Measures  
=====

First Aid:EYES OR  
SKIN:IMMEDIATELY FLUSH SKIN OR EYES W/PLENTY OF WATER  
FOR 15 MIN & GET MED ATTN FOR EYES;INH:IF DIFFICULT IN  
BREATHING,REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED & GET MED  
ATTN.

=====  
Fire Fighting Measures  
=====

Flash Point:NONE  
Lower Limits:NONE  
Upper Limits:NONE  
Extinguishing Media:CO\*2,FOAM,DRY CHEM  
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP;COOL EXPSD CONTNRS  
W/WATER SPRAY  
Unusual Fire/Explosion Hazard:SPILL/RUNOFF MAY CAUSE POL  
LUTION,FIRE  
&/OR EXPLOSION HAZARDS;EXPOSED CONTNRS MAY EXPLODE IN FIRE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ELIM IGN SOURCES.USE PROTECTV EQUIP,PROVIDE  
VENT.STOP LEAK W/O RISK.DIKE LG SPILL & PUMP INTO COVRD  
DRUMS;ABSORB/CONTAIN SMALL SPILL IN CONTNR PENDING DISPOSAL;MFR  
RECOMMENDS,NEUTRLZ W/SOD BICARBONATE THEN FLUSH TO SEWER W/LG AMT  
H\*2O IAW EXISTG REGS.

=====  
Handling and Storage  
=====

=====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.

Other Precautions:AVOID PROLONGED/REPEATED CONTACT W/PRODUCT;REMOVE & WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE;APPROX PH OF PRODUCT:0.7;UNIT CONTNR QTY 5 GAL IS TO MAKE 20 GAL WORKING SOLN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQD IN NORMAL CONDITIONS

Ventilation:MECH

ANICAL(GEN) IF NEEDED

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES

Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

MSDS FM MFR DTD:2/21/78;REISSUED:3/79:PER MFR LTR 8/18/82,RECORDAK MICROFILM BLEACH/REPLNSHR WAS RENAMED "KODAK MICROFILM BLEACH & REPLENISHER"(DATE UNKNOWN)PROBABLY BEFORE 2/78;SEE ADDL DATA.

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:>212 F

Vapor Pres:17

Va

por Density:0.6

Spec Gravity:1.14

Solubility in Water:COMPLETE

Appearance and Odor:REDDISH-BROWN; ODORLESS

Percent Volatiles by Volume:85.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

BASES(CAUSTICS), FLAMMABLE LIQUIDS,OXIDIZERS

Stability Condition to Avoid:UNK

Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERD CONTNRS PENDING DISPOSAL

.SHIP

WASTE TO NEUTRALZNG/DISPOSAL AREA IAW DOT/EPA REGS.HANDLE/DISPOSE  
OF IAW FED,STATE/LOCAL REGS;MFR SUGGESTS:NEUTRALZ W/SODIUM  
BICARBONATE THEN FLUSH TO SEWE R W/LG AMT H\*2O.FED STATE/LOCAL LAWS  
TAKE PRECEDEN

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accur  
ate and

disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.