

EASTMAN KODAK COMPANY -- 180 5134 RP X-OMAT FIXER & REPLR, PART A -- 6525-01-076-8677

=====  
Product Identification  
=====

Product ID:180 5134 RP X-OMAT FIXER & REPLR, PART A

MSDS Date:11/14/1991

FSC:6525

NIIN:01-076-8677

Kit Part:Y

MSDS Number: BGKQT

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716

-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====  
Composition/Information on Ingredients  
=====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 40-45%

Other REC Limits:NONE SPECIFIED

Ingred Name:AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:X

N6465000  
Fraction by Wt: 35-40%  
Other REC Limits:NONE SPECIFIED

Ingred Name:SODIUM THIOSULFATE  
CAS:7772-98-7  
RTECS #:XN6476000  
Fraction by Wt: 10-15%  
Other REC Limits:NONE SPECIFIED

Ingred Name:AMMONIUM ACETATE (SARA III)  
CAS:631-61-8  
RTECS #:AF3675000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:AMMONIUM BISULFITE (SARA III)  
CAS:10192-30-0  
RTECS #:WT3595000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM BISULFITE (SASA III)  
CAS:7631-90-5  
RTECS #:VZ2000000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3; 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM ACETATE  
CAS:126-96-5  
RTECS #:AJ4375000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT ESTABLISHED.  
Routes of Entry: Inhalation:NO Sk

in:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MANUFACTURER STATES THAT THIS MATERIAL IS EXPECTED TO BE A LOW HAZARD BY INHALATION, EYE AND SKIN CONTACT, AND INGESTION. MAY CAUSE IRRITATION OF EYES.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:SLIGHT IRRITATION AND REDNESS OF EYES.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS

OR WITH A PRE-EXISTING DISEASE INVOLVING THE SKIN MAY BE AT INCREASED RISK FROM EXPOSURE.

=====  
===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES HOLDING EYELIDS OPEN. GET IMMEDIATE MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING AND SHOES. WASH SKIN WITH SOAP AND WATER. GET MEDICAL ATTENTION. INGESTION:DRINK 1-2 GLASSES OF WATER. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. CALL A PHYSICIAN AT ONCE.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL AS APPROPRIATE FOR SURROUNDINGS.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE RESIDUE WITH LARGE AMOUNTS OF WATER BY FLUSHING TO THE SEWER. DISCHARGE MAY BE GOVERNED BY LOCAL LAW.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE AND AWAY FROM STRONG ACIDS, BASES OR OXIDIZING AGENTS

NTS.  
Other Precautions:AVOID CONTACT WITH EYES. WASH THOROUGHLY AFTER HANDLING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AN APPROPRIATE NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPOR SHOULD BE WORN IF MIST IS CREATED.  
Ventilation:MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE.  
Protective Gloves:NEOPRENE OR NATURAL RUBBER  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.  
INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.  
Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health  
THIS IS PART A OF TWO PART KIT. PART #180 5134 IS FOR MAKING 200 GALLONS OF SOLUTION. EACH UNIT PACKAGE CONTAINS 50 GAL.

===== Physical/Chemical Properties =====

HCC:C3  
Boiling Pt:B.P. Text:>212F,>100C  
Vapor Pres:18 @20C  
Vapor Density:0.6  
Spec Gravity:1.361  
pH:4.10  
Solubility in Water:COMPLETE  
Appearance and Odor:COLORLESS SOLUTION; SLIGHT AMMONIA ODOR  
Percent Volatiles by Volume:45

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS, STRONG ACIDS, STRONG BASES  
Stability Condition to Avoid:STRONGLY ACID OR BASIC  
Hazardous Decomposition Products:CARBON DIOXIDE AND PROBABLY CARBON MONOXIDE AS WELL AS AMMONIA

AND OXIDES OF SULFUR AND NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.