

TEXACO, INC. -- 940 REGAL AFB 2 -- 9150-01-086-8127

===== Product Identification =====

Product ID:940 REGAL AFB 2

MSDS Date:01/01/1985

FSC:9150

NIIN:01-086-8127

MSDS Number: BGLDW

=== Responsible Party ===

Company Name:TEXACO, INC.

Emergency Phone Num:914-831-3400 X-406

CAGE:EO421

=== Contractor Identification ===

Company Name:TEXACO INC CORPORATE HQ

Address:2000 WESTCHESTER AVE

City:WHITE PLAINS

State:NY

ZIP:10604

Country:US

Phone:914-253-4000

CAGE:59595

Company Name:TEXACO, INC.

Box:509

CAGE:EO421

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: >85%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ARYL AMINE

Fraction by Wt: 1-5%

Ingred Name:ALKYL AMINE

Fraction by Wt: 1-5%

Ingred Name:ADDITIVES

Ingred Name:LITHIUM

CAS:7439-93-2

RTECS #:OJ5540

=====
Hazards Identification
=====

Effects of Overexposure:EYES & SKIN: MILD IRRIT INHAL:MILD IRRIT IF NOT
IN EXCESS OF PERMISSIBLE CONCENTRATIONS.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH W/ PLENTY OF WATER FOR 15 MINUTES. SKIN: WASH W/
SOAP AND WATER, SEVERAL TIMES DAILY. INHAL: REMOVE FROM EXPOSURE.

=====
Fire Fighting Measures
=====

Flash Point:N/D FOR GREAS
ES

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, ALCOHOL FOAM, CO*2

Fire Fighting Procedures:USE H*2O TO COOL FIRE-EXPOSED CANS.

Unusual Fire/Explosion Hazard:WATER OR FOAM MAY CAUSE FROTHING. CO,
CO*2, ALDEHYDES, KETONES AND COMBUSTION PROD OF N AND S FORM.

=====
Accidental Release Measures
=====

Spill Release Procedures:CONTAIN SPILL. ABSORB W/ INERT POROUS
MATERIAL. IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO
DISPERSE VAPORS AND TO PROVIDE
PROTECTION FOR PERSONS ATTEMPTING TO
STOP THE LEAK.

=====
Handling and Storage
=====

Handling and Storage Precautions:PERIODS OF EXPOSURE TO HIGH TEMPS
SHOULD BE MINIMIZED. MAXIMUM USABLE TEMPERATURE IS 250F;121C.

Other Precautions:EXERCISE REASONABLE PERSONAL CLEANLINESS.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE REQUIRED (MFR).

Ventilation:NORMAL VENTILATION

Eye Protection:GOGGLES OR FACE SHIE

LD

Other Protective Equipment:LAUNDRER SOILED WORK CLOTHING AT LEAST WEEKLY.

Supplemental Safety and Health

CONTAINER: 120 LB DRUM. VAPOR PRESSURE: NIL. N/D= NOT DETERMINED.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:N/D

Evaporation Rate & Reference:N/D

Solubility in Water:NEGLIGIBLE

Appearance and Odor:TAN COLOR

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Hazardous Decompositio

n Products:CO,CO*2,ALDEHYDES,KETONES,COMBUSTION
PROD OF N AND SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECOMMENDS: DISPOSE AS AN OILY WASTE.

CONTACT A WASTE OIL CONTRACTOR OR DISPOSAL SPECIALIST IF NECESSARY.

DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.