

AM MULTIGRAPHICS -- 32-4656, TONER REMOVER (ISSUED 6/2/83), 83-7-101013 --  
6850-01-090-6557

===== Product Identification =====

Product ID:32-4656, TONER REMOVER (ISSUED 6/2/83), 83-7-101013

MSDS Date:09/01/1986

FSC:6850

NIIN:01-090-6557

MSDS Number: BGLLC

=== Responsible Party ===

Company Name:AM MULTIGRAPHICS

Address:1800 W CENTRAL ROAD

City:MOUNT PROSPECT

State:IL

ZIP:60056-2293

Country:US

Info

Phone Num:708-870-5121/708-870-5087

Emergency Phone Num:708-870-5121 (DAY) 398-1900 (NIGHT)

CAGE:0FTL5

=== Contractor Identification ===

Company Name:AM MULTIGRAPHICS

Address:1800 WEST CENTRAL ROAD

City:MT. PROSPECT

State:IL

ZIP:60056

Country:US

Phone:708-5121/ EVEN 708-398-1900

CAGE:0FTL5

Company Name:AM MULTIGRAPHICS DIV OF AM INTL INC

Address:431 LAKEVIEW CT

Box:City:MOUNT PROSPECT

State:IL

ZIP:60056-6048

Country:US

Phone:847-375-1700

CAGE:09177

===== Composition/Information on Ing

redients =====

Ingred Name:2-METHOXYETHYL ACETATE (EGMEA)

CAS:110-49-6

RTECS #:KL5950000

Fraction by Wt: 70%

OSHA PEL:S, 25 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 30%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

===== Hazards Identification =====

Effects of Overexposure:

VAPORS CAUSE NARCOSIS.SEVERE EYE IRRIT.

MODERATE SKIN IRRIT.

===== First Aid Measures =====

First Aid:INHALATION,REMOVE TO FRESH AIR. EYE CONT:FLUSH WITH WATER 15  
MIN,CONSULT PHYSICIAN. SKIN:FLUSH WITH WATER. INGESTION: MEDICAL  
TREATMENT IS REQUIRED.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:132F/55C (TCC)

Extinguishing Media:STANDARD MEDIA FOR SOLVENT FIRE

Fire Fighting Procedures

:WEAR NIOSH/MSHA APPROVED PRESSURE DEMAND SCBA

AND FULL PROTECTIVE EQUIPMENT . DO NOT USE WATER STREAM.

Unusual Fire/Explosion Hazard:THERMAL DECOMPOSITION PRODUCTS MAY

INCLUDE HCL & PHOSGENE . IN COMMON W/ALL CHLORINATED HYDROCARBONS,  
FORMS PHOSGENE WHEN PASSING THROUGH FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQUATE VENTILATION,FLUSH WITH  
WATER.WHEN SPILLED,SOLVENT BECOMES INCREASINGLY FLAMMABLE

=====

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN COOL PLACE AWAY FROM  
HEAT,SPARKS OR OPEN FLAME.

Other Precautions:WASH HANDS AFTER USE. IF SPILLED SOLVENT BECOMES  
INCREASINGLY FLAMMABLE.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH  
EXPOSURE OF CONCERN

Ventilation:LOCAL EXHAUST

Eye Protection:CHEM GOGGLES

Supplemental Safety and Health

KEY1

:J1.

=====  
Physical/Chemical Properties  
=====

HCC:F4

Boiling Pt:B.P. Text:165F/73C

Spec Gravity:1.196

Evaporation Rate & Reference:2.4 (BUTYL ACETATE=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR LIQUID

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

=====  
Disposal Considerations  
=====

Waste

Disposal Methods:IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume resp

onsibility for the suitability of this information to their particular situation.