

FISKE BROS REFINING CO -- 18901 LUBRIPLATE MAG-1, MAG-00 -- 9150-01-095-5512

=====
Product Identification
=====

Product ID:18901 LUBRIPLATE MAG-1, MAG-00

MSDS Date:05/01/1987

FSC:9150

NIIN:01-095-5512

MSDS Number: BGLPN

=== Responsible Party ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:8038

City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Info Phone Num:201-589-9150

Emergency

Phone Num:201-589-9150

Preparer's Name:ROBERT J. SIBILIA

CAGE:73219

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:INDUSTRIAL SUPPLY CORP

Address:1905 WESTWOOD AVE

Box:6356

City:RICHMOND

State:VA

ZIP:23230

Country:US

Phone:804-355-8041
CAGE:6A908

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL
Other REC Limits:NONE SPECIFIED
OSHA PEL:5MG/M3 (OIL MIST)
ACGIH TLV:5MG/M3 (OIL MIST)

Ingred Name:LITHIUM SOAP
Other REC Limits:NONE SPECIFIED

Ingred Name:ADDITIVES (NOT SPECIFIED)
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO
IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT WITH EYES MAY CAUSE IRRITATION. MINUTE AMOUNTS OF PRODUCT ASPIRATED INTO LUNGS THROUGH EITHER INHALATION OR VOMITING MAY CAUSE CHEMICAL PNEUMOCONIOSIS, WHICH CAN DAMAGE LUNGS OR BE FATA L. PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN IRRITATION.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:INHALED: NONE STATED. EYE S: REDNESS, DISCOMFORT. SKIN: REDNESS, DISCOMFORT. INGESTED: NONE STATED.
Medical Cond Aggravated by Exposure:NONE NOTED.

=====
First Aid Measures
=====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP & WATER.IF INJECTED UNDER SKIN, SEE DOCTOR IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF B ODY. INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. INGESTION: DO NOT INDUCE V

OMITING! SEE DOCTOR IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:335F,168C

Lower Limits:0.9%

Upper Limits:7.0%

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, OR WATER SPRAY

Fire Fighting Procedures:COOL FIRE EXPOSED CONTAINERS WITH WATER. WEAR SELF-CONTAINED BREATHING APPARATUS IN ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT,DRILL OR WELD EMPTY CONTAINERS AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION. USE SUITABLE ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL. KEEP OUT OF WATER WAYS AND SEWERS. IF ENTERS WATERWAYS OR SEWER, CALL NATIONAL RESPONSE CENTER AT 800-4 24-8802.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:S

TORE IN COOL DRY AND WELL VENTILATED

AREA AWAY FROM HEAT, OPEN FLAMES, OXIDIZERS. KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:AVOID CONTACT WITH EYES,SKIN AND CLOTHES. DO NOT BREATHE VAPORS OR MIST. DO NOT USE CONTAMINATED CLOTHES. WASH THOROUGHLY AFTER EACH USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. IF EMERGENCY OCCURS; USE NIOSH/MSHA APPROVED RESPIRATOR OR SUPPLIED AIR RESPIRATOR OR SCBA,

AS REQUIRED. USE IAW 29 CFR 1910.134 AND RESPIRATOR MANUFACTURER'S RECOMMENDATIONS.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW PEL/TLV FOR OIL MIST.

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:OIL RESISTENT APRON, IF NEEDED. HMIS: EYE WASH AVAILABLE.

Work Hygienic Practices:AVOID BREATHING MIST. REMOVE OIL-SOAKED CLOTHING & LAUNDER BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CON

TACT.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>550F,>288C
Vapor Pres:5 (AIR=1)
Spec Gravity:0.88 (WATER=1)
Evaporation Rate & Reference: