View NSN Online: https://aerobasegroup.com/nsn/5970-01-099-1446

GENERAL ELECTRIC CO., SILICONE -- RTV108, SILICONE RUBBER SEALANT

MSDS Safety Information

FSC: 5970

NIIN: 01-099-1446 MSDS Date: 02/12/1993 MSDS Num: BGLSL

Product ID: RTV108, SILICONE RUBBER SEALANT

MFN: 01

Responsible Party Cage: 01139

Name: GENERAL ELECTRIC CO., SILICONE PRODUCT DIV.

Address: HUDSON RIVE

R ROAD

City: WATERFORD NY 12188

Info Phone Number: 518-237-3330/266-2641

Emergency Phone Number: 518-237-3330/FAX (73) 518-233-3795

Preparer's Name: DA POLSINELLI

Proprietary Ind: Y Review Ind: Y Published: Y

Contractor Summary

Cage: 01139

Name: GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address: 260 HUDSON RIVER RD City: WATERFORD NY 12188

Phone: 518-237-3330/800-332-3390

C

age: 3R262

Name: SAN DIEGO SEAL CO Address: 7635 RONSON RD City: SAN DIEGO CA 92111

Phone: 619-278-3270

Item Description Information

Item Manager: S9G

Item Name: INSULATING COMPOUND, ELECTRICAL

Specification Number: NONE Type/Grade/Class: NONE

Unit of Issue: TU

Quantitative Expression: 00000000003OZ

UI Container Qty: 0
Type of Container: TUBE

========

Ingredients

Name: *** PROPRIETARY ***

Health Hazards Data

LD50 LC50 Mixture: UNKNOWN Route Of Entry Inds - Inhalation: YES

Skin: YES Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: INGESTION- MAY BE HARMFUL. SKIN- UNCURED PRODUCT CONTACT

WILL IRR

ITATE LIPS, GUMS, TONGUE AND SKIN. INHALATION- CAUSES IRRITATION OF

THE MOUTH, NOSE AND THROAT. EYES- UNCURED PRODUCT CONTACT IRRITA TES EYES.

Signs And Symptions Of Overexposure: IRRITATE LIPS, GUMS, TONGUE, EYES

Medical Cond Aggravated By Exposure: NONE KNOWN

First Aid: INGESTION- RINSE MOUTH WITH WATER SEVERAL TIMES. SKIN- REMOVE COMPLETELY WITH A DRY CLOTH OR PAPER TOWEL, BEFORE WASHING WITH DETERGENT AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHAL ATION- MOVE PERSON

TO FRESH AIR. EYES-IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

Handling and Disposal

Spill Release Procedures: WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL AND PUT IN A CONTAINER FOR DISPOSAL. WASH WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE SLIPPING HAZARD. WEAR PROPER PROTECTIVE EQUIPMENT AS SPECIFIE D IN

THE PROTECTIVE EQUIPMENT SECTION.INCREASE AREA VENTILATION.

Neutralizing Agent: NONE

Waste Disposal Methods: DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Handling And Storage Precautions: REMOVE CONTACT LENSES BEFORE USING SEALANT. DO NOT HANDLE LENSES UNTIL ALL SEALANT HAS BEEN CLEANED FROM THE FINGERTIPS, NAILS AND CUTICLES.RESIDUAL SEALANT MAY REMAIN ON FINGERS FOR SEVERAL DAYS AND TRANSFER TO LENSES AND CAUSE SEVERE IRRITATION.

Other Precaut

ions: USE MECHANICAL VENTILATION TO STAY BELOW TLV OF 10 PPM ACETIC ACID.UNCURRED PRODUCT CONTACT IRRITATES EYES,SKIN. USE IN WELL VENTILATED AREA TO PREVENT IRRITATION BY VAPORS.

Fire and Explosion Hazard Information

Extinguishing Media: ALL STANDARD FIREFIGHTING MEDIA.

Fire Fighting Procedures: NONE KNOWN. Unusual Fire/Explosion Hazard: NONE NOTED

Control Measures

Respiratory Protection: USE ONLY IN WELL VENTILATED AREA.

Ventilation: USE ONLY IN WELL VENTILATED AREA.

Protective Gloves: CLOTH GLOVES. Eye Protection: SAFETY GLASSES.

Other Protective Equipment: EYEWASH STATIONS

Work Hygienic Practices: WASH HANDS THOROUGHLY AFTER HANDLING THIS MATERIAL.

Supplemental Safety and Health: NONE

Physical/Chemica

I Properties

HCC: N1

Vapor Pres: UNK Vapor Density: UNK Spec Gravity: 1.06

PH: N/A/

VOC Grams/Liter: 65 Solubility in Water: NEGL

Appearance and Odor: PASTE, TRANSLUCENT, ACETIC ACID ODOR.

Percent Volatiles by Volume: <8

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: NONE

Materials To Avoid: NONE

Hazar

dous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, SILICON DIOXIDE, ACETIC ACID, FORMALDEHYDE. Hazardous Polymerization Indicator: NO
Toxicological Information
Ecological Information
MSDS Transport Informa tion
======================================
Other Information
Transportation Information
Responsible Party Cage: 01139 T rans ID NO: 107235 Product ID: RTV108, SILICONE RUBBER SEALANT MSDS Prepared Date: 02/12/1993 Review Date: 05/05/1987 MFN: 1 Net Unit Weight: 10.3 OZ Multiple KIT Number: 0 Review IND: Y Unit Of Issue: TU Container QTY: 0 Type Of Container: TUBE
Detail DOT Information
DOT PSN Code: ZZZ DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION ===================================

Detail IMO Information

IMO PSN Code: ZZZ

IMO Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

Detail IATA Information

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Detail AFI Informat

ion

AFI PSN Code: ZZZ

AFI Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

HAZCOM Label

Product ID: RTV108, SILICONE RUBBER SEALANT

Cage: 01139

Company Name: GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Street: 260 HUDSON RIVER RD

City: WATERFORD NY

Zipcode: 12188

Health Emergency Phone: 518-237-3330/FA

X (73) 518-233-3795 Label Required IND: Y

Date Of Label Review: 02/15/1994

Status Code: C

Label Date: 02/15/1994 Origination Code: F Eye Protection IND: YES Signal Word: CAUTION Health Hazard: Slight Contact Hazard: Slight Fire Hazard: None Reactivity Hazard: None

Hazard And Precautions: INGESTION- MAY BE HARMFUL. SKIN- WILL IRRITATE LIPS,

GUMS, TONGUE AND SKIN. INHALATION- CAUSES IRRITATION OF THE MOUTH, NOSE AND THROAT. EYES- IRRITATES EYES. REMOVE CONTACT LENSES BEFORE USING SEA LANT.

FIRST AID: INGESTION- RINSE MOUTHWITH WATER SEVERAL TIMES. SKIN- REMOVE COMPLETELY WITH A DRY CLOTH OR PAPER TOWEL, BEFORE WASHING WITH DETERGENT AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION- MOVE PERSON TO FRESH AIR. EYES- IMMEDIATELY FLUSH WITHPLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

Disclaimer (provided with this information by the compiling agencies): T his

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who

is not a military or civilian employee of the

United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.