View NSN Online: https://aerobasegroup.com/nsn/8040-01-107-3981

CLICK BOND, INC. -- KA1-E1-CP-125-000-005-A1A1 PATCH KIT -- 8040-01-107-3981

============= Product Identification ========================

Product ID:KA1-E1-CP-125-000-005-A1A1 PATCH KIT

MSDS Date:01/12/1989

FSC:8040

NIIN:01-107-3981

Kit Part:Y

MSDS Number: BGMFB === Responsible Party ===

Company Name: CLICK BOND, INC. Address: 2151 LOCKHEED WAY

City: CARSON CITY

State:NV

ZIP:89706-0713

Country:US

Info Phone Num:702-885-8000

Emergency Phone Num:702-885-8000 Preparer's Name:CHARLES G. HUTTER, III

CAGE:DO144

=== Contractor Identification ===

Company Name: CLICK BOND DIV OF PHYSICAL SYSTEMS INC

Address:2151 LOCKHEED WAY

Box:City:CARSON CITY

State:NV

ZIP:89701-0713 Country:US

Phone:775-885-8000

CAGE:66530

Company Name: CLICK BOND, INC. Address: 2151 LOCKHEED WAY

City: CARSON CITY

State:NV

ZIP:89706-0713 Phone:702-885-8000

CAGE:DO144

======= Composition/Information on Ingredients ========

Ingred Name: ITEM IS T

========== Hazards Identification ===========
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHALATION SLIGHTLY TOXIC-CAN CAUSE IRRITATION TO RESPIRATORY TRACT, OVER EXPOSURE, DELAYED LUNG DAMAGE. CHEMICAL PNEUMONIA. CORROSIVE TO EYE TISSUE LEAD TO PERMANENT INJURY/BLINDNESS. INGESTION: SLIG HTLY TOXIC. MAY CAUSE SKIN IRRITATION.
======================================
First Aid:INHALATION: REMOVE TO FRESH AIR, GIVE OXYGEN IF BREATHING DIFFICULT. EYES: FLUSH WITH WATER FOR 15 MIN, LIFTING LIDS. GET IMMEDIATE MEDICAL CARE. INGESTION: DO NOT INDUCE VOMITING. TAKE LARGE AMOUNTS OF WATER/MILK, GET MEDICAL CARE. SKIN; WIPE EXCESS FROM SKIN AND WASH WITH WATER FOR 15 MIN THEN USE SOAP AND WATER.
============= Fire Fighting Measures =============
Flash Point:270 F/132 C Extingui shing Media:WATER SPRAY, DRY CHEMICAL, FOAM, CARBON DIOXIDE Fire Fighting Procedures:WATER TO COOL FIRE-EXPOSED CONTAINERS. NON-BURNING USEWATER SPRAY TO DISPERSE VAPORS, PROVIDES PROTECTION TO THOSE STOPPING LEAK. Unusual Fire/Explosion Hazard:WEAR SELF-CONTAINED BREATHING APPARATUS AND GOGGLES. WATER OR FOAM MAY CAUSE FROTHING.
========= Accidental Release Measures ==========
Spill Release Procedures:AVOID PERSONAL CONTACT. CONTAIN SPILL IF POSSIBLE. WIPE U P OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP. CLEAN UP WITH SUITABLE VENTILATION.
============ Handling and Storage =============
Handling and Storage Precautions:MIX WELL. STORE IN A COOL, DRY PLACE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:SELF-CONTAINED BREATHING APPARATUS IN HIGH CONCENTRATION AREAS. Ventilation:LOCAL EXHAUST RECOMMENDED. Supplemental Safety and Health
======== Physical/Chemical P

RADE SECRET

roperties =========
Spec Gravity:1.13 Viscosity:7000 Solubility in Water:PARTIAL
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES OXIDIZING AGENTS; STRONG MINERAL ACIDS; STRONG LEWIS ACIDS; ACIDS HALOGENATED ORGANIC COMPOUNDS.
======= Disposal Considerations ==========
Waste Disposal Methods:CONTROLLED INCINERATION OR BURY IN LEGAL LANDFILL. COMPLY WITH LOCAL, STATE AND FEDERAL ENVIRONME

NTAL

PROTECTION AGENCY REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.