View NSN Online: https://aerobasegroup.com/nsn/9150-01-113-2047

Product ID:FYRQUEL 220-MLT MSDS Date:01/01/1987 FSC:9150 NIIN:01-113-2047 MSDS Number: BGMJX === Responsible Party === Company Name:STAUFFER CHEMICAL COMPANY Emergency Phone Num:(203) 226-6602 CAGE:8F554 === Contractor Identification === Company Name:STAUFFER CHEMICAL CO SPECIALTY CHEMICAL DIVISION

Address:NYALA FARMS RD Box:City:WESTPORT State:CT ZIP:06880 Country:US Phone:203-226-6602/CHEMTREC 800-424-9300 CAGE:8F554

Ingred Name: BUTYLATED TRIPHENYL PHOSPHATE ESTERS (MIXED ISOMERS)

Ingred Name:TRIPHENYL PHOSPHATE CAS:115-86-6 RTECS #:TC8400000 OSHA PEL:3 MG/M3 ACGIH TLV:3 MG/M3; 9192

Ingred Name: ADDITIVES, TYPE NOT SPECIFIED - LESS THAN 1%.

Effec

## ts of Overexposure:RESP.IRRITANT; DYSPNEA,PULMONARY EDEMA;SKIN & EYE IRRIT; POSSIBLE CHOLINESTERASE INHIBITION (RBC)

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP&WATER. RMV CONTAM CLTHG&SHOES. INGEST:INDUCE VOMIT. RPT UNTIL VOMIT IS C LEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

Flash Point:475F, 246C (COC)

- Extinguishing Media:CO\*2, DRY CHEMICAL, FOAM, WATER. TO REMOVE FLAME SOURCE.
- Fire Fighting Procedures:WEAR FULL-FACE SELF-CONTAINED BREATHING APP/IMPERV. CLOTHING
- Unusual Fire/Explosion Hazard:FLUID MAY SUPPORT COMBUSTION & DECOMP YIELDING TOXIC PRODUCTS (EG; PHOSPHORUS OXIDES)

Spill Release Procedures: VENTILATE AREA. WEAR PROTECTIVE CLOTHING TO

PREVENT SKIN & EYE CONTACT. SOAK UP LIQ.W/SUITABLE ABSORBENT MATL (EG: SAWDUST, CLAY, VERMICULITE). SWEEP MATL & PLACE IN SEALED STEEL CONTAINER. LARGE SPIL LS SHOULD BE DYKED & PUMPED TO SALVAGE.

Handling and Storage Precautions:STORE IN COOL, DRY, WELL-VENTILATED AREAS AWAY FROM FLAMMABLE MATLS, HEAT/FLAME SOURCES & FOODSTUFFS. CARBON STEEL IS PREFERRED MATL FOR CONTAINERS.
Other Precautions:EXPOSURE MAY CAUS
E CHOLINESTERASE INHIBITION. ATROPINE IV IS ANTIDOTAL. 2-PAM IS ALSO ANTIDOTAL WHEN ADMINISTERED EARLY & IN CONJUCTION WITH ATROPINE.// FLUID MAY SOFTEN SOME PLASTICS.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR OIL MIST/VAPORS Ventilation:RECOMMENDED ESP IF USE CONDITIONS GENERATE AEROSOLS/VAPORS. Protective Gloves:IMPERVIOUS Eye Protection:SPLASH-PROOF GOGGLES Other Protective Equipment:SAFE

## TY SHOWER & EYE BATH Supplemental Safety and Health UPDATE PER NON-OSHA HCS MSDS DTD OCT 84

HCC:V6 Vapor Pres:0.1 Spec Gravity:1.15 Evaporation Rate & amp; Reference:COLORLESS, CLEAR L Solubility in Water:NEGLIGIBLE Appearance and Odor:IQUID WITH ESSENTIALLY NO ODOR.
======================================
<ul> <li>Stability Indicator/Materials to Avoid:YES</li> <li>MOISTURE, ACIDIC OR ALKALINE CONDITIONS. VERY HIG</li> <li>H TEMPS.</li> <li>Stability Condition to Avoid:TEMP &gt;150F &amp; MOISTURE COMBINE TO CAUSE SLOW HYDROLYSIS.</li> <li>Hazardous Decomposition Products:PHENOL, ALKYL PHENOLS, ARYL PHOSPORIC ACIDS WHEN HYDROLYZED.</li> <li>Conditions to Avoid Polymerization:IN ABSENCE OF MOISTURE, FLUID REMAINS STABLE TO HIGH TEMPS.</li> </ul>
======================================

Waste Disposal Methods: FOLLOW FED, STATE & LOCAL REGULATIONS. MFR RECOMMENDS DISPOSAL OF SEALED CONTAINERS IN AN APPROVED LANDFILL,

INCINERATION BY A LICENSED OPERATOR W/APPROPRIATE POLLUTION CONTROLS, OR SALVAGE & RECLAMAT ION IF QUANTITY JUSTIFIES. RECLAMATION PREFERRED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.