View NSN Online: https://aerobasegroup.com/nsn/8010-01-120-2877

DEVOE MARINE COATINGS CO. -- DEVRAN 219 #27 HAZE GRAY BASE (MD1865)

8010-01-120-2877

Product ID:DEVRAN 219 #27 HAZE GRAY BASE (MD1865)

MSDS Date:01/01/1987

FSC:8010

NIIN:01-120-2877

Kit Part:Y

MSDS Number: BGMRL === Responsible Party ===

Company Name: DEVOE MARINE COATINGS CO.

Address:4000 DUPONT CIR

Box:7600

City:LOUISVILLE

State:KY ZIP:40207 Country:US CAGE:

EO141

=== Contractor Identification ===

Company Name: DEVOE AND RAYNOLDS CO DIV OF GROW GROUP INC

Address:4000 DUPONT CIR

Box:7600

City:LOUISVILLE

State:KY ZIP:40207 Country:US

Phone:502-361-2536/502-589-9340

CAGE:6R552

Company Name: DEVOE MARINE COATING CO.

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:EO141

====== Composition/Information on Ingredients ========

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR2 275000

Fraction by Wt: 15%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name: MAGNESIUM SILICATE (CAS # 14807-96-6) (PEL-20MPPCF)

(TLV-GIVEN FOR RESPIRABLE DUST)

RTECS #:VV7720000 Fraction by Wt: 20% ACGIH TLV:2 MG/CUM

Ingred Name: METHYL N-AMYL KETONE

CAS:110-43-0

RTECS #:MJ5075000 Fraction by Wt: 20% OSHA PEL:100 PPM ACGIH TLV:50 PPM; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000 Fraction by Wt: 15%

OSHA PEL:100 PPM/150 STEL

ACGIH

TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 120F/NEAR FIRE, OPEN

FLAME.SEE OSHA 1910.106.CLOSE CAN AFT USE.DONT REUSE EMPTY CAN.DONT SMOKE.VAPS MAY CAUSE FLASH FIRE/IGNIT EXPLOSIVLY

Other Precautions:SPECL FIRE FIGHT:H*2O,PREFER FOG NOZZ.COOL FIRE EXPOS CNTNR W/H*2O TO PREV PRESSURE BLDUP/AUTOIGNITION. VENTILATN:& DECOMP PRODUCTS.VAPS MAY SPREAD.PREV BLDUP-REMOVE VAPS FROM LOWR

LVL OF AREA

===== Exposure Controls/Personal Protection ========

Respiratory Protection:NIOSH/MSHA APPRVD:MECHANICAL FILTER RESPIRATR IN OUTDOOR/OPEN AREAS;CHEMICAL/MECHANICAL FILTER IN RESTRICT (SEE SUPP DAT)

Ventilation:GENERAL DILUTION/LOCAL EXHAUST IN VOL,PATTERN TO KEEP AIR CONTAM CONC 1

Spec Gravity:1.3618

Evaporation Rate & Deference: SLOWER THAN ETHER

Percent Volatiles by Volume:59.7

======== Stability and Reactivity Data ========

=====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT W/STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:HEAT TO DECOMP:MAY CAUSE HAZ FUMES
THAT MAY CONTAIN CO,CO*2.

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL,STATE & FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.